

## Dr Haixue Yan

PhD, PGCAP, CEng, FIMMM and FRSC

School of Engineering and Materials Science  
Queen Mary University of London  
Mile End Road  
London E1 4NS

tel: +44 (0)20 7882 5164

email: h.x.yan@qmul.ac.uk web: www.sems.qmul.ac.uk/h.x.yan

---

### 2026

**Enhanced piezoelectric properties of  $\text{Pb}(\text{Ni}_{1/3}\text{Nb}_{2/3})\text{O}_3$  -  $\text{Pb}(\text{Yb}_{1/2}\text{Nb}_{1/2})\text{O}_3$  -  $\text{Pb}(\text{Zr},\text{Ti})\text{O}_3$  ceramics by the design of multiphase coexistence.**

. *Journal of The European Ceramic Society* vol. 46, (5).Elsevier.

**Grain Size-Dependent Defect and Domain Evolution in Lead Titanate-Based Relaxor Ferroelectrics.**

. *Acs Applied Materials & Interfaces* vol. 18, (17) 24889-24898.American Chemical Society (Acs).

**Structural Origin of Morphotropic Phase Boundary in Advanced Perovskite Ferroelectric Oxides.**

. *Journal of The American Chemical Society*.American Chemical Society (Acs).

**Susceptible Antiferroelectric/Ferroelectric Transitions in Silver Niobate-Based Ceramics Induced by Manual Mechanical Processing.**

. *Inorganic Chemistry* vol. 65, (6) 3215-3224.American Chemical Society (Acs).

**Flexible Ultrasound Sensor Based on ErPMNPT Ceramics for Vascular Monitoring.**

. *IEEE Sensors Journal* vol. 26, (9) 13915-13925.Institute of Electrical and Electronics Engineers (IEEE).

### 2025

**Strategic optimization of polar nanoregions for superior dielectric tunability in PMNPT-based ceramics.**

. *Journal of The European Ceramic Society* vol. 45, (16).Elsevier.

**Dynamic Atomistic Polar Structure Underpins Ultrahigh Linear Electro-Optic Coefficient in Transparent Ferroelectric Ceramics.**

. *Journal of The American Chemical Society*.American Chemical Society (Acs).

**Lead-free piezoelectric ceramics with ultralow mechanical quality factor.**

. *Materials Research Bulletin* vol. 191,.Elsevier.

**Engineering polar nanoclusters for enhanced microwave tunability in ferroelectric thin films.**

. *Nature Communications* vol. 16, (1).Springer Nature.

**High entropy engineered polymer blends with enhanced dielectric properties and high temperature stability.**

. *Nature Communications* vol. 16, (1).Springer Nature.

**Review of enhancing thermal conductivity in polymer-based dielectrics as passive components.**

. *Progress in Polymer Science* vol. 169,.Elsevier.

**Boosting the electrocaloric effect with broad working temperature span in lead-free relaxor ferroelectrics through disorder modulation.**

. *Applied Physics Letters* vol. 127, (12).Aip Publishing.

**Lead-Free  $(1-x)\text{Ba}(\text{Zr}_{0.2}\text{Ti}_{0.8})\text{O}_3-x(\text{Ba}_{0.7}\text{Ca}_{0.3})\text{TiO}_3$  Based Ferroelectrics with Diffuse Phase Transitions for Sustainable Electrocaloric Applications.**

. *The Journal of Physical Chemistry C* vol. 129, (38) 17229-17235.American Chemical Society (Acs).

---

**Effect of Samarium Doping on the Energy Storage Properties of Bismuth Sodium Titanate-Based Lead-Free Ceramics.**

. *Acs Applied Materials & Interfaces* vol. 17, (38) 53780-53790. American Chemical Society (Acs).

**Relationships between structure and properties in commercial lead zirconate titanate (PZT) piezoceramics.**

. *Journal of Materiomics* vol. 11, (5). Elsevier.

**Direct magnetoelectric coupling from magnetically/ferroelectrically active cation in low-symmetry octahedron.**

. *Physical Review B* vol. 112, (5). American Physical Society (Aps).

**Tunable and anomalous electrocaloric behaviors in Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>-based relaxor enabled by dynamics of polar nanoregions.**

. *Acta Materialia* vol. 293, Elsevier.

**Phase Transitions in Bi/Ca Modified AgNbO<sub>3</sub> Ceramics with Excellent Energy Storage Density and Storage Intensity.**

. *Small* vol. 21, (32). Wiley.

**Enhanced electrocaloric effect in lead-free relaxor ferroelectrics via point defect engineering.**

. *Applied Physics Letters* vol. 126, (23). Aip Publishing.

**Dislocation-nanoparticle interactions in TiB<sub>2</sub>p/Cu composites based on molecular dynamics and experiments.**

. *Journal of Alloys and Compounds* vol. 1033, Elsevier.

**Low cost small scale recycling aluminium cans for energy conservation and environmental sustainability.**

. *Environmental Technology* vol. 46, (22) 4575-4582. Taylor & Francis.

**Boosting energy density by frustration.**

. *Science China Materials* vol. 68, (6) 2148-2149. Springer Nature.

**Unveiling the mechanism of substitution-induced high piezoelectric performance in PLZT ceramics.**

. *Journal of Advanced Ceramics*. Tsinghua University Press.

**Phase transformation in lead titanate based relaxor ferroelectrics with ultra-high strain.**

. *Nature Communications* vol. 16, (1). Springer Nature.

**Investigation of electric field-induced phase transitions in unfilled tungsten bronze relaxor ceramics designed by the high entropy concept.**

. *Acta Materialia* vol. 284, Elsevier.

**Healing filler/matrix interfaces in drawn BN/UHMWPE composites by a simple thermal annealing treatment.**

. *Rsc Applied Polymers* vol. 3, (2) 361-369. Royal Society of Chemistry (Rsc).

**Optimization of Thermoelectric Transport Properties in Nanocomposite MgAgSb-Based Alloys.**

. *Journal of Inorganic Materials*. Shanghai Institute of Ceramics.

**Non-volatile voltage-controlled magnetization in single-phase multiferroic ceramics at room temperature.**

. *Journal of Materiomics* vol. 11, (1). Elsevier.

**2024**

**Ferroelectric anomaly of perovskite layer structured Pb<sup>2+</sup>-doped Sr<sub>2</sub>Nb<sub>2</sub>O<sub>7</sub> ceramics.**

. *Journal of The American Ceramic Society* vol. 107, (6) 3989-3999.

**Processing and characterisation of hot rolling pressed PVDF films with enhanced field-induced polarisation.**

. *Polymer* vol. 302,.

**High Thermoelectric Performance Related to PVDF Ferroelectric Domains in P-Type Flexible PVDF-Bi<sub>0.5</sub>Sb<sub>1.5</sub>Te<sub>3</sub> Composite Film.**

. *Small* vol. 20, (19).

**Dielectric probing of low-temperature degradation resistance of commercial zirconia bio-ceramics.**

. *Dental Materials* vol. 40, (6) 921-929.Elsevier.

**Dielectric relaxation and conductivity phenomena in ferroelectric ceramics at high temperatures.**

. *Journal of The European Ceramic Society* vol. 44, (5) 2886-2902.

**Microwave tunability in tin substituted barium titanate.**

. *Journal of The European Ceramic Society* vol. 44, (3) 1627-1635.Elsevier.

**Origin of Polarization in Bismuth Sodium Titanate-Based Ceramics.**

. *Journal of The American Chemical Society* vol. 146, (8) 5569-5579.American Chemical Society (Acs).

**High-temperature dielectric polymer composite for high power energy storage applications.**

. *Science China Chemistry* vol. 67, (8) 2425-2426.Springer Nature.

**Microstructure evolution and the deformation mechanism in nanocrystalline superior-deformed tantalum.**

. *Nanoscale* vol. 16, (9) 4826-4840.Royal Society of Chemistry (Rsc).

## 2023

**Structure and dielectric properties in Mg/Nb co-substituted bismuth sodium titanate.**

. *Journal of Alloys and Compounds* vol. 969,.Elsevier.

**Energy storage properties of samarium-doped bismuth sodium titanate-based lead-free ceramics.**

. *Chemical Engineering Journal* vol. 473,.

**BROADBAND DIELECTRIC CHARACTERIZATION OF CARBON BLACKREINFORCED NATURAL RUBBER.**

. *Rubber Chemistry and Technology* vol. 96, (4) 656-666.Rubber Division, Acs.

**Fundamentals, advances and perspectives of piezocatalysis: A marriage of solid-state physics and catalytic chemistry.**

. *Progress in Materials Science* vol. 138,.

**Microwave characterization of two Ba 0.6 Sr 0.4 TiO 3 dielectric thin films with out-of-plane and in-plane electrode structures.**

. *Journal of Advanced Ceramics* vol. 12, (8) 1521-1532.Tsinghua University Press.

**Structure and Conductivity in LISICON Analogues within the Li<sub>4</sub>GeO<sub>4</sub>Li<sub>2</sub>MoO<sub>4</sub> System.**

. *Inorganic Chemistry* vol. 62, (30) 11876-11886.American Chemical Society (Acs).

**Simultaneous Increase in Dielectric Breakdown Strength and Thermal Conductivity of Oriented UHMWPE Containing Diamond Nanoparticles.**

. *Macromolecules* vol. 56, (20) 8183-8191.American Chemical Society (Acs).

**Enhanced piezoelectricity in Na and Ce co-doped CaBi<sub>4</sub>Ti<sub>4</sub>O<sub>15</sub> ceramics for high-temperature applications.**

. *Journal of Advanced Ceramics* vol. 12, (7) 1331-1344.

**Structural evolution and coexistence of ferroelectricity and antiferromagnetism in Fe, Nb co-doped BaTiO<sub>3</sub> ceramics.**

. *Journal of The European Ceramic Society* vol. 43, (6) 2460-2468.Elsevier.

**High-entropy MTiO<sub>3</sub> perovskite oxides with glass-like thermal conductivity for thermoelectric applications.**

. *Journal of Alloys and Compounds* vol. 937,.Elsevier.

**Magnetolectric coupling at microwave frequencies observed in bismuth ferrite-based multiferroics at room temperature.**

. *Journal of Material Science and Technology* vol. 137, 100-103.Elsevier.

**Achieving Ultrahigh Energy Storage Density of La and Ta Codoped AgNbO<sub>3</sub> Ceramics by Optimizing the Field-Induced Phase Transitions.**

. *Acs Applied Materials & Interfaces* vol. 15, (3) 4246-4256.American Chemical Society (Acs).

**Effect of Ag<sup>+</sup> doping and Ag addition on the thermoelectric properties of KSr<sub>2</sub>Nb<sub>5</sub>O<sub>15</sub>.**

. *Ceramics International* vol. 49, (2) 1731-1741.Elsevier.

**Deciphering the peculiar hysteresis loops of 0.05Pb(Mn<sub>1/3</sub>Sb<sub>2/3</sub>)O<sub>3</sub>0.95Pb(Zr<sub>0.52</sub>Ti<sub>0.48</sub>)O<sub>3</sub> piezoelectric ceramics.**

. *Acta Materialia* vol. 244,.Elsevier.

**Origin of the switchable photocurrent direction in BiFeO<sub>3</sub> thin films.**

. *Materials Horizons* vol. 10, (12) 5892-5897.Royal Society of Chemistry (Rsc).

2022

**Local Structure in BIMEVOXes (ME = Ge, Sn).**

. *Chemistry of Materials* vol. 35, (1) 189-206.American Chemical Society (Acs).

**Antiferroelectric-like Behavior in a Lead-Free Perovskite Layered Structure Ceramic.**

. *Inorganic Chemistry* vol. 61, (50) 20316-20325.American Chemical Society (Acs).

**Grain orientation evolution and multi-scale interfaces enhanced thermoelectric properties of textured Sr<sub>0.9</sub>La<sub>0.1</sub>TiO<sub>3</sub> based ceramics.**

. *Journal of The European Ceramic Society* vol. 42, (15) 7017-7026.Elsevier.

**In-situ growth of carbon nanotubes on ZnO to enhance thermoelectric and mechanical properties.**

. *Journal of Advanced Ceramics* vol. 11, (12) 1932-1943.Tsinghua University Press.

**Stability of 3Y-TZP nano zirconia powder after hydrothermal ageing treatment.**

. *Advances in Applied Ceramics* vol. 121, (5-8) 159-165.Sage Publications.

**Terahertz Faraday Rotation of SrFe<sub>12</sub>O<sub>19</sub>Hexaferrites Enhanced by Nb Doping.**

. *Acs Applied Materials and Interfaces* vol. 14, (41) 46738-46747.

**Dielectric polymer composites with ultra-high thermal conductivity and low dielectric loss.**

. *Composites Science and Technology* vol. 229,.Elsevier.

**Effect of composition on the dielectric properties and thermal conductivity of -SiAlON ceramics.**

. *Journal of Materials Science: Materials in Electronics* vol. 33, (28) 22480-22491.Springer Nature.

**Low thermal conductivity in A-site high entropy perovskite relaxor ferroelectric.**

. *Applied Physics Letters* vol. 121, (11).Aip Publishing.

**Enhancement of Thermoelectric Performance in Bi<sub>0.5</sub>Sb<sub>1.5</sub>Te<sub>3</sub> Particulate Composites Including Ferroelectric BaTiO<sub>3</sub> Nanodots.**

. *Acs Applied Materials & Interfaces* vol. 14, (32) 37204-37212.American Chemical Society (Acs).

**A novel high-entropy perovskite ceramics Sr<sub>0.9</sub>La<sub>0.1</sub>(Zr<sub>0.25</sub>Sn<sub>0.25</sub>Ti<sub>0.25</sub>Hf<sub>0.25</sub>)O<sub>3</sub> with low thermal conductivity and high Seebeck coefficient.**

. *Journal of The European Ceramic Society* vol. 42, (8) 3480-3488.Elsevier.

**Temperature dependence in ageing process in commercial zirconia dental ceramics.**

. *Advances in Applied Ceramics* vol. 121, (4) 150-153.Sage Publications.

**Low-cost Free-standing ferroelectric polymer films with high polarization produced via pressing-and-folding.**

. *Journal of Materiomics* vol. 8, (3) 640-648.Elsevier.

**Effect of La<sup>3+</sup>, Ag<sup>+</sup> and Bi<sup>3+</sup> doping on thermoelectric properties of SrTiO<sub>3</sub>: First-principles investigation.**

. *Ceramics International* vol. 48, (10) 13803-13816.Elsevier.

**Chemical Solution Deposition of SinglePhase BiFeO<sub>3</sub> Thin Films on Transparent Substrates.**

. *Solar Rrl* vol. 6, (7).Wiley.

**Phase transformations in an Aurivillius layer structured ferroelectric designed using the high entropy concept.**

. *Acta Materialia* 117815-117815.Elsevier.

**Enhanced energy storage performance under low electric field in Sm<sup>3+</sup> doped AgNbO<sub>3</sub> ceramics.**

. *Journal of Materiomics* vol. 8, (2) 266-273.Elsevier.

**Reduced lattice thermal conductivity of perovskite-type high-entropy (Ca<sub>0.25</sub>Sr<sub>0.25</sub>Ba<sub>0.25</sub>RE<sub>0.25</sub>)TiO<sub>3</sub> ceramics by phonon engineering for thermoelectric applications.**

. *Journal of Alloys and Compounds* vol. 898,.Elsevier.

**Local Structure and Conductivity in the BIGAVOX System.**

. *The Journal of Physical Chemistry C* vol. 126, (4) 2108-2120.American Chemical Society (Acs).

**Temperature-dependent deformation in silver-particle-covered copper nanowires by molecular dynamics simulation.**

. *Journal of Materiomics* vol. 8, (1) 68-78.Elsevier.

**Exploration about superior anti-counterfeiting ability of Sm<sup>3+</sup> doped K<sub>2</sub>Sr<sub>2</sub>Nb<sub>5</sub>O<sub>15</sub> photochromic ceramics: Origin and atomic-scale mechanism.**

. *Journal of Materiomics* vol. 8, (1) 38-46.Elsevier.

**High-entropy (Ca<sub>0.2</sub>Sr<sub>0.2</sub>Ba<sub>0.2</sub>La<sub>0.2</sub>Pb<sub>0.2</sub>)TiO<sub>3</sub> perovskite ceramics with A-site short-range disorder for thermoelectric applications.**

. *Journal of Material Science and Technology* vol. 97, 182-189.Elsevier.

**Local structure in a tetravalent-substituent BIMEVOX system: BIGEVOX.**

. *Journal of Materials Chemistry A* vol. 10, (7) 3793-3807.Royal Society of Chemistry (Rsc).

**Ultra-high energy density integrated polymer dielectric capacitors.**

. *Journal of Materials Chemistry A* vol. 10, (18) 10171-10180.Royal Society of Chemistry (Rsc).

**Silver niobate perovskites: structure, properties and multifunctional applications.**

. *Journal of Materials Chemistry A* vol. 10, (28) 14747-14787.Royal Society of Chemistry (Rsc).

## 2021

**Grain Size Effects in Mn-Modified 0.67BiFeO<sub>3</sub>0.33BaTiO<sub>3</sub> Ceramics.**

. *Acs Applied Materials & Interfaces* vol. 13, (48) 57548-57559.American Chemical Society (Acs).

**Terahertz Characterization of Lead-Free Dielectrics for Different Applications.**

. *Acs Applied Materials & Interfaces* vol. 13, (45) 53492-53503.American Chemical Society (Acs).

**Terahertz probing of low temperature degradation in zirconia bioceramics.**

. *Journal of The American Ceramic Society*.

**Facile one-step synthesis and enhanced photocatalytic activity of WC/ferroelectric nanocomposite.**

. *Journal of Materials Chemistry A*.Royal Society of Chemistry (Rsc).

**Characterization of microwave and terahertz dielectric properties of single crystal La<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub> along one single direction.**

. *Journal of The European Ceramic Society*.

**Cationic polymer brush-coated bioglass nanoparticles for the design of bioresorbable RNA delivery vectors.**

. *European Polymer Journal* vol. 156,.Elsevier.

**Electric field-induced transformations in bismuth sodium titanate-based materials.**

. *Progress in Materials Science* vol. 122,.Elsevier.

**Structural Evolution in BiNbO<sub>4</sub>.**

. *Inorganic Chemistry: Including Bioinorganic Chemistry*.American Chemical Society.

**Terahertz Reading of Ferroelectric Domain Wall Dielectric Switching.**

. *Acs Applied Materials & Interfaces*.American Chemical Society (Acs).

**Grain orientation evolution and thermoelectric properties of textured (Ca<sub>0.87</sub>Ag<sub>0.1</sub>La<sub>0.03</sub>)<sub>3</sub>Co<sub>4</sub>O<sub>9</sub> ceramics prepared by tape casting.**

. *Ceramics International* vol. 47, (6) 8365-8374.Elsevier.

**Investigation of transitions between the M-phases in AgNbO<sub>3</sub> based ceramics.**

. *Journal of Materials Chemistry A*.Royal Society of Chemistry.

**Effect of processing on the structures and properties of bismuth sodium titanate compounds.**

. *Journal of Materials Research* 1-11.Springer.

**Multi elements substituted Aurivillius phase relaxor ferroelectrics using high entropy design concept.**

. *Materials and Design* 109447-109447.Elsevier.

**Response to comment on point defect structure of La-doped SrTiO<sub>3</sub> ceramics with colossal permittivity.**

. *Scripta Materialia* vol. 190, 118-120.

**Tunable phase transitions in NaNbO<sub>3</sub> ceramics through bismuth/vacancy modification.**

. *Journal of Materials Chemistry C* vol. 9, (12) 4289-4299.Royal Society of Chemistry (Rsc).

## 2020

**Temperature-dependent deformation processes in two-phase TiAl+Ti<sub>3</sub>Al nano-polycrystalline alloys.**

. *Materials & Design* vol. 199, 109422-109422.

**Ultrafast Electric Field-Induced Phase Transition in Bulk Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub> under High-Intensity Terahertz Irradiation.**

. *Acs Photonics*.American Chemical Society.

**Perovskite Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>-based materials for dielectric capacitors with ultrahigh thermal stability.**

. *Materials and Design* 109344-109344.Elsevier.

**High Tunability and Low Loss in Layered Perovskite Dielectrics through Intrinsic Elimination of Oxygen Vacancies.**

. *Chemistry of Materials*.American Chemical Society (Acs).

**Low-loss High Entropy Relaxor-like Ferroelectrics with A-site Disorder.**

. *Journal of The European Ceramic Society*.Elsevier.

**Structure and dielectric properties of double A-site doped bismuth sodium titanate relaxor ferroelectrics for high power energy storage applications.**

. *Journal of Materials Chemistry A*.Royal Society of Chemistry.

**Multiscale understanding of electric polarization in poly(vinylidene fluoride)-based ferroelectric polymers.**

. *Journal of Materials Chemistry C*.Royal Society of Chemistry.

**Phase transitions in RbPrNb<sub>2</sub>O<sub>7</sub>, a layer structured ferroelectric with a high Curie point.**

. *Acta Materialia* vol. 200, 971-979.Elsevier.

**Polar nano-clusters in nominally paraelectric ceramics demonstrating high microwave tunability for wireless communication.**

. *Journal of The European Ceramic Society* vol. 40, (12) 3996-4003.Elsevier.

**Enhanced dielectric properties of highly dense Ba<sub>0.5</sub>Sr<sub>0.5</sub>TiO<sub>3</sub> ceramics via non-toxic gelcasting.**

. *Journal of Materials Science: Materials in Electronics* vol. 31, (20) 17819-17827.Springer Nature.

**Publisher's Note: Room-temperature multiferroic behavior in layer-structured Aurivillius phase ceramics [Appl. Phys Lett. 117, 052903 (2020)].**

. *Applied Physics Letters* vol. 117, (9).Aip Publishing.

**Solution-Processed Epitaxial Growth of Arbitrary Surface Nanopatterns on Hybrid Perovskite Monocrystalline Thin Films.**

. *Acs Nano* vol. 14, (9) 11029-11039.American Chemical Society (Acs).

**Room-temperature multiferroic behavior in layer-structured Aurivillius phase ceramics.**

. *Applied Physics Letters* vol. 117, (5) 052903-052903. AIP Publishing.

**Ultrahigh field-induced strain in lead-free ceramics.**

. *Nano Energy* 105037-105037. Elsevier.

**Giant energy storage density in PVDF with internal stress engineered polar nanostructures.**

. *Nano Energy* vol. 72, Elsevier.

**Cobalt-induced structural modulation in multiferroic Aurivillius-phase oxides.**

. *Journal of Materials Chemistry C. Royal Society of Chemistry (Rsc)*.

**Colossal thermoelectric enhancement in  $\text{Cu}_{2+x}\text{Zn}_1\text{Sn}_4$  solid solution by local disordering of crystal lattice and multi-scale defect engineering.**

. *Journal of Materials Chemistry A* vol. 8, (21) 10909-10916. Royal Society of Chemistry.

**High Thermoelectric Performance in SnTe Nanocomposites with All-Scale Hierarchical Structures.**

. *Acs Applied Materials and Interfaces. American Chemical Society*.

**Boosting the Thermoelectric Performance of Calcium Cobaltite Composites through Structural Defect Engineering.**

. *Acs Applied Materials & Interfaces* vol. 12, (19) 21623-21632. American Chemical Society (Acs).

**The Contribution of Electrical Conductivity, Dielectric Permittivity and Domain Switching in Ferroelectric Hysteresis Loops.**

. *Progress in Advanced Dielectrics 1-20. World Scientific Publishing*.

**Ferroelectrics: Terahertz Probing Irreversible Phase Transitions Related to Polar Clusters in  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$  Based Ferroelectric (Adv. Electron. Mater. 4/2020).**

. *Advanced Electronic Materials* vol. 6, (4). Wiley.

**Terahertz Probing Irreversible Phase Transitions Related to Polar Clusters in  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$  Based Ferroelectric.**

. *Advanced Electronic Materials* 1901373-1901373. Wiley.

**Interactive human-machine learning framework for modelling of ferroelectric-dielectric composites.**

. *Journal of Materials Chemistry C* vol. 8, (30) 10352-10361. Royal Society of Chemistry (Rsc).

**Domain Wall Free Polar Structure Enhanced Photodegradation Activity in Nanoscale Ferroelectric  $\text{Ba}_x\text{Sr}_{1-x}\text{TiO}_3$ .**

. *Advanced Energy Materials* vol. 10, (38).

## 2019

**Microstructure and thermoelectric performance of  $\text{La}_{0.9}\text{Ag}_{0.1}\text{Co}_4\text{O}_9$ /nanosized Ag composite ceramics.**

. *International Journal of Ceramic Engineering & Science* vol. 2, (1) 7-16. Wiley.

**Dielectric and ferroelectric properties of BTFCO thin films.**

. *Journal of Electroceramics* vol. 43, (1-4) 92-95. Springer Nature.

**Ultrahigh -phase content poly(vinylidene fluoride) with relaxor-like ferroelectricity for high energy density capacitors.**

. *Nature Communications* vol. 10, (1). Springer Nature.

**Isolation of a ferroelectric intermediate phase in antiferroelectric dense sodium niobate ceramics.**

. *Acta Materialia* vol. 179, 255-261. Elsevier Bv.

**Relaxor behavior and photocatalytic properties of  $\text{BaBi}_2\text{Nb}_2\text{O}_9$ .**

. *Journal of The American Ceramic Society. Wiley*.

**Symmetry-mode analysis for intuitive observation of structure-property relationships in the lead-free antiferroelectric (1-x)AgNbO<sub>3</sub>xLiTaO<sub>3</sub>.**

. *Iucrj* vol. 6, (Pt 4) 740-750. *International Union of Crystallography (Iucr)*.

**Multiferroic properties of single phase Bi<sub>3</sub>NbTiO<sub>9</sub> based textured ceramics.**

. *Journal of Alloys and Compounds* vol. 788, 701-704.

**Spark plasma sintering of grain-oriented Sr<sub>2</sub>Bi<sub>4</sub>Ti<sub>5</sub>O<sub>18</sub> aurivillius phase ceramics.**

. *Journal of Alloys and Compounds* vol. 782, 6-9.

**Orthoenstatite to forsterite phase transformation in magnesium germanate ceramics.**

. *Ceramics International* vol. 45, (6) 7878-7884.

**Microstructure and broadband dielectric properties of Zn<sub>2</sub>SiO<sub>4</sub> ceramics with nano-sized TiO<sub>2</sub> addition.**

. *Ceramics International*.

**Twostep processing of thermoelectric (Ca<sub>0.9</sub>Ag<sub>0.1</sub>)<sub>3</sub>Co<sub>4</sub>O<sub>9</sub>/nanosized Ag composites with high ZT.**

. *Journal of The European Ceramic Society*.

**Remarkably enhanced polarisability and breakdown strength in PVDF-based interactive polymer blends for advanced energy storage applications.**

. *Polymer* vol. 168, 246-254.

**Point defect structure of La-doped SrTiO<sub>3</sub> ceramics with colossal permittivity.**

. *Acta Materialia* vol. 164, 76-89. *Elsevier*.

**On the origin of grain size effects in Ba(Ti<sub>0.96</sub>Sn<sub>0.04</sub>)O<sub>3</sub> perovskite ceramics.**

. *Journal of The European Ceramic Society*.

**Phase transitions in tantalum-modified silver niobate ceramics for high power energy storage.**

. *Journal of Materials Chemistry A* vol. 7, (2) 834-842.

**Bi<sub>2</sub>Fe<sub>4</sub>O<sub>9</sub> thin films as novel visible-light-active photoanodes for solar water splitting.**

. *Journal of Materials Chemistry A* vol. 7, (16) 9537-9541. *Royal Society of Chemistry (Rsc)*.

**Silver niobate based lead-free ceramics with high energy storage density.**

. *Journal of Materials Chemistry A* vol. 7, (17) 10702-10711. *Royal Society of Chemistry (Rsc)*.

## 2018

**Crystal structure and electrical properties of textured Ba<sub>2</sub>Bi<sub>4</sub>Ti<sub>5</sub>O<sub>18</sub> ceramics.**

. *Journal of The European Ceramic Society*.

**Enhanced piezoelectric properties and electrocaloric effect in novel lead-free (Bi<sub>0.5</sub>K<sub>0.5</sub>)TiO<sub>3</sub>-La(Mg<sub>0.5</sub>Ti<sub>0.5</sub>)O<sub>3</sub> ceramics.**

. *Journal of The American Ceramic Society* vol. 101, (12) 5503-5513.

**Preparation and mechanical performance of graphene platelet reinforced titanium nanocomposites for high temperature applications.**

. *Journal of Alloys and Compounds* vol. 765, 1111-1118.

**Microstructure characterization and thermoelectric properties of Sr<sub>0.9</sub>La<sub>0.1</sub>TiO<sub>3</sub> ceramics with nano-sized Ag as additive.**

. *Journal of Alloys and Compounds* vol. 762, 80-89.

**Enhanced thermoelectric performance of Sn-doped Cu<sub>3</sub>SbS<sub>4</sub>.**

. *Journal of Materials Chemistry C* vol. 6, (31) 8546-8552.

**Electric-field-induced local distortion and large electrostrictive effects in lead-free NBT-based relaxor ferroelectrics.**

. *Journal of The European Ceramic Society*.

**Crystal Chemistry and Magnetic Properties of Gd-Substituted Aurivillius-Type Bi<sub>5</sub>FeTi<sub>3</sub>O<sub>15</sub> Ceramics.**

. *Journal of Physical Chemistry C* vol. 122, (27) 15733-15743.

**Perovskite Sr<sub>x</sub>(Bi<sub>1-x</sub>Na<sub>0.97x</sub>Li<sub>0.03</sub>)<sub>0.5</sub>TiO<sub>3</sub> ceramics with polar nano regions for high power energy storage.**

. *Nano Energy* vol. 50, 723-732.

**SrFe<sub>2</sub>O<sub>19</sub> based ceramics with ultra-low dielectric loss in the millimetre-wave band.**

. *Applied Physics Letters* vol. 112, (14). Aip Publishing.

**Bi<sub>3.25</sub>La<sub>0.75</sub>Ti<sub>2.5</sub>Nb<sub>0.25</sub>(Fe<sub>0.5</sub>Co<sub>0.5</sub>)<sub>0.25</sub>O<sub>12</sub>, a single phase room temperature multiferroic.**

. *Journal of Materials Chemistry C* vol. 6, (11) 2733-2740.

**Enhanced dielectric tunability and energy storage properties of plate-like Ba<sub>0.6</sub>Sr<sub>0.4</sub>TiO<sub>3</sub>/poly(vinylidene fluoride) composites through texture arrangement.**

. *Composites Science and Technology* vol. 158, 112-120.

## 2017

**Giant electrostrain accompanying structural evolution in lead-free NBT-based piezoceramics.**

. *Journal of Materials Chemistry C* vol. 6, (4) 814-822.

**Phase evolution and electrical behaviour of samarium-substituted bismuth ferrite ceramics.**

. *Journal of The European Ceramic Society*.

**Phase composition and temperature dependence of electrocaloric effect in leadfree**

**Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>BaTiO<sub>3</sub>(Sr<sub>0.7</sub>Bi<sub>0.20.1</sub>)TiO<sub>3</sub> ceramics.**

. *Journal of The European Ceramic Society* vol. 37, (15) 4732-4740. Elsevier.

**Ordered coalescence of nano-crystals in alkaline niobate ceramics with high remanent polarization.**

. *Journal of Materiomics* vol. 3, (4) 267-272.

**Phase transitions in bismuth-modified silver niobate ceramics for high power energy storage.**

. *Journal of Materials Chemistry A* vol. 5, (33) 17525-17531.

**Titanium Dioxide Engineered for Near-dispersionless High Terahertz Permittivity and Ultra-low-loss.**

. *Scientific Reports* vol. 7, (1). Springer Nature.

**Type I pseudofirstorder phase transition induced electrocaloric effect in leadfree Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>0.06BaTiO<sub>3</sub> ceramics.**

. *Applied Physics Letters* vol. 110, (18). Aip Publishing.

**Microstructural comparison of effects of hafnium and titanium additions in spark-plasma-sintered Fe-based oxide-dispersion strengthened alloys.**

. *Journal of Nuclear Materials* vol. 487, 433-442. Elsevier.

**Effect of Phase Transitions on Thermal Depoling in Lead-Free 0.94(Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>)<sub>0.06</sub>(BaTiO<sub>3</sub>) Based Piezoelectrics.**

. *The Journal of Physical Chemistry C* vol. 121, (10) 5709-5718. American Chemical Society (Acs).

**Terbium-induced phase transitions and weak ferromagnetism in multiferroic bismuth ferrite ceramics.**

. *Journal of Materials Chemistry C* vol. 5, (10) 2669-2685. Royal Society of Chemistry (Rsc).

**Topochemical transformation of two-dimensional single crystalline Na<sub>0.5</sub>Bi<sub>0.5</sub>TiO<sub>3</sub>BaTiO<sub>3</sub> platelets from Na<sub>0.5</sub>Bi<sub>4.5</sub>Ti<sub>4</sub>O<sub>15</sub> precursors and their piezoelectricity.**

. *Journal of Materials Chemistry A* vol. 5, (30) 15780-15788. Royal Society of Chemistry (Rsc).

## 2016

**Theory-Guided Synthesis of an Eco-Friendly and Low-Cost Copper Based Sulfide Thermoelectric Material.**

. *The Journal of Physical Chemistry C* vol. 120, (48) 27135-27140. American Chemical Society (Acs).

**Carriers concentration tailoring and phonon scattering from n-type zinc oxide (ZnO) nanoinclusion in p- and n-type bismuth telluride (Bi<sub>2</sub>Te<sub>3</sub>): Leading to ultra low thermal conductivity and excellent thermoelectric properties.**

. *Journal of Alloys and Compounds* vol. 694, 864-868.

**Lead free Bi<sub>3</sub>TaTiO<sub>9</sub> ferroelectric ceramics with high Curie point.**

. *Materials Letters* vol. 175, 79-81. Elsevier.

**Tuning the electrocaloric enhancement near the morphotropic phase boundary in lead-free ceramics.**

. *Scientific Reports* vol. 6, (1). Springer Nature.

**Strain-Dependent Dielectric Behavior of Carbon Black Reinforced Natural Rubber.**

. *Macromolecules* vol. 49, (6) 2339-2347. American Chemical Society (Acs).

**Efficacy of lone-pair electrons to engender ultralow thermal conductivity.**

. *Scripta Materialia* vol. 111, 49-53.

**Room temperature magnetoelectric coupling in intrinsic multiferroic Aurivillius phase textured ceramics.**

. *Dalton Transactions* vol. 45, (36) 14049-14052. Royal Society of Chemistry (Rsc).

**Growth of SiC platelets using contactless flash technique.**

. *Journal of The Ceramic Society of Japan* vol. 124, (9) 845-847. Ceramic Society of Japan.

**High energy density in silver niobate ceramics.**

. *Journal of Materials Chemistry A* vol. 4, (44) 17279-17287. Royal Society of Chemistry (Rsc).

## 2015

**Crystallographic Structure and Ferroelectricity of (A<sub>x</sub>La<sub>1-x</sub>)<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub> (A = Sm and Eu) Solid Solutions with High T<sub>c</sub>.**

. *Journal of The American Ceramic Society* vol. 99, (2) 523-530. Wiley.

**A High Curie Point Ferroelectric Ceramic Ca<sub>3</sub>(VO<sub>4</sub>)<sub>2</sub>.**

. *Ferroelectrics* vol. 487, (1) 94-100. Taylor & Francis.

**Processing and microstructure characterisation of oxide dispersion strengthened Fe<sub>14</sub>Cr<sub>0.4</sub>Ti<sub>0.25</sub>Y<sub>2</sub>O<sub>3</sub> ferritic steels fabricated by spark plasma sintering.**

. *Journal of Nuclear Materials* vol. 464, 61-68. Elsevier.

**Role of synthesis method on microstructure and mechanical properties of graphene/carbon nanotube toughened Al<sub>2</sub>O<sub>3</sub> nanocomposites.**

. *Ceramics International* vol. 41, (8) 9813-9822.

**Dielectric relaxation and electrical conductivity in Ca<sub>5</sub>Nb<sub>4</sub>TiO<sub>17</sub> ceramics.**

. *Ceramics International* vol. 41, (8) 9923-9930.

**Unfolding grain size effects in barium titanate ferroelectric ceramics.**

. *Scientific Reports* vol. 5, (1). Springer Nature.

**Effect of Ca substitution sites on dielectric properties and relaxor behavior of Ca doped barium strontium titanate ceramics.**

. *Journal of Materials Science Materials in Electronics* vol. 26, (4) 2486-2492.

**Study on properties of tantalum-doped La<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub> ferroelectric ceramics.**

. *Journal of Advanced Dielectrics* vol. 5, (01). World Scientific Publishing.

**Reduced thermal conductivity by nanoscale intergrowths in perovskite like layered structure La<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub>.**

. *Journal of Applied Physics* vol. 117, (7). Aip Publishing.

**Microwave and terahertz dielectric properties of MgTiO<sub>3</sub>-CaTiO<sub>3</sub> ceramics.**

. *Materials Letters* vol. 138, 225-227.

**Ferroelectricity in DionJacobson ABiNb<sub>2</sub>O<sub>7</sub> (A = Rb, Cs) compounds.**

. *Journal of Materials Chemistry C* vol. 3, (1) 19-22. Royal Society of Chemistry (Rsc).

**Enhancement of electric field-induced strain in BaTiO<sub>3</sub> ceramics through grain size optimization.**

. *Physica Status Solidi (a) Applications and Materials Science* vol. 212, (2) 433-438.

**Effect of different templates on structure evolution and large strain response under a low electric field in -textured lead-free BNT-based piezoelectric ceramics.**

. *Journal of The European Ceramic Society* vol. 35, (9) 2489-2499.

## 2014

**Ferroelectric and dielectric properties of Nd<sub>2x</sub>CexTi<sub>2</sub>O<sub>7</sub> ceramics.**

. *Advances in Applied Ceramics* vol. 114, (4) 191-197. Sage Publications.

**Low Temperature Magnetic and Dielectric Anomalies in Rare Earth Substituted BiFeO<sub>3</sub> Ceramics.**

. *Journal of The American Ceramic Society* vol. 97, (12) 3729-3732. Wiley.

**Short range polar state transitions and deviation from Rayleigh-type behaviour in Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>-based perovskites.**

. *Applied Physics Letters* vol. 105, (10).

**Three Layer Perovskite Like Structured Pr<sub>3</sub>Ti<sub>2</sub>TaO<sub>11</sub> Ferroelectrics with Super High Curie Point.**

. *Journal of The American Ceramic Society* vol. 97, (11) 3624-3630. Wiley.

**Spark plasma sintering of alumina composites with graphene platelets and silicon carbide nanoparticles.**

. *Advanced Engineering Materials* vol. 16, (9) 1111-1118.

**Enhancement of thermoelectric properties by atomic-scale percolation in digenite Cu<sub>x</sub>S.**

. *Journal of Materials Chemistry A* vol. 2, (25) 9486-9489.

**Large ZT enhancement in hot forged nanostructured p-type Bi<sub>0.5</sub>Sb<sub>1.5</sub>Te<sub>3</sub> bulk alloys.**

. *Journal of Materials Chemistry A* vol. 2, (16) 5785-5790.

**Lithium-induced phase transitions in lead-free Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub> based ceramics.**

. *Journal of Physical Chemistry C* vol. 118, (16) 8564-8570.

**Effect of dysprosium substitution on crystal structure and physical properties of multiferroic BiFeO<sub>3</sub> ceramics.**

. *Journal of The European Ceramic Society* vol. 34, (3) 641-651.

**Utilizing the phonon glass electron crystal concept to improve the thermoelectric properties of combined Yb-stuffed and Te-substituted CoSb<sub>3</sub>.**

. *Scripta Materialia* vol. 72-73, 63-66.

**High field ZnO varistors prepared by spark plasma sintering.**

. *Advances in Applied Ceramics* vol. 113, (2) 94-97.

**Reply to the Comment on The Effect of Barium Substitution on the Ferroelectric Properties of Sr<sub>2</sub>Nb<sub>2</sub>O<sub>7</sub> Ceramics [J. Am. Ceram. Soc., 96 [4] 1163-1170 (2013)].**

. *Journal of The American Ceramic Society* vol. 97, (2) 662-663.

## 2013

**MgAl<sub>2</sub>O<sub>4</sub>-LaCr<sub>0.5</sub>Mn<sub>0.5</sub>O<sub>3</sub> composite ceramics for high temperature NTC thermistors.**

. *Journal of Materials Science Materials in Electronics* vol. 24, (11) 4452-4456.

**Effect of grain size on domain structures, dielectric and thermal depoling of Nd-substituted bismuth titanate ceramics.**

. *Applied Physics Letters* vol. 103, (18).

**Effects of zinc substitution on the dielectric properties of Ca<sub>5</sub>Nb<sub>4</sub>TiO<sub>17</sub> microwave ceramics.**

. *Journal of Advanced Dielectrics* vol. 3, (04). World Scientific Publishing.

**Effect of donor dopants cerium and tungsten on the dielectric and electrical properties of high Curie point ferroelectric strontium niobate.**

. *Ceramics International* vol. 39, (7) 7669-7675.

**Mechanical properties of graphene platelet-reinforced alumina ceramic composites.**

. *Ceramics International* vol. 39, (6) 6215-6221.

**Dielectric relaxation, lattice dynamics and polarization mechanisms in Bi<sub>0.5</sub>Na<sub>0.5</sub>TiO<sub>3</sub>-based lead-free ceramics.**

. *Journal of Applied Physics* vol. 114, (1).

**Microwave dielectric properties of CaO-La<sub>2</sub>O<sub>3</sub>-Nb<sub>2</sub>O<sub>5</sub>-TiO<sub>2</sub> ceramics.**

. *Journal of Materials Science Materials in Electronics* vol. 24, (6) 1947-1954.

**Piezoelectric and dielectric properties of Ce substituted La<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub> ceramics.**

. *Journal of The European Ceramic Society* vol. 33, (5) 1001-1008.

**The effect of barium substitution on the ferroelectric properties of Sr<sub>2</sub>Nb<sub>2</sub>O<sub>7</sub> Ceramics.**

. *Journal of The American Ceramic Society* vol. 96, (4) 1163-1170.

**Reverse boundary layer capacitor model in glass/ceramic composites for energy storage applications.**

. *Journal of Applied Physics* vol. 113, (2).

**Effect of donor dopants cerium and tungsten on the dielectric and electrical properties of high Curie point ferroelectric strontium niobate.**

. *Ceramics International*.

**Ferroelectricity of Pr<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub> ceramics with super high Curie point.**

. *Advances in Applied Ceramics* vol. 112, (2) 69-74.

**Effect of Fe Substitution on Thermoelectric Properties of Fe<sub>x</sub>In<sub>4-x</sub>Se<sub>3</sub> Compounds.**

. *Journal of Electronic Materials* vol. 42, (4) 675-678.

**Active ferroelectricity in nanostructured multiferroic BiFeO<sub>3</sub> bulk ceramics.**

. *Journal of Materials Chemistry C* vol. 1, (36) 5628-5631.

**Contribution of piezoelectric effect, electrostriction and ferroelectric/ferroelastic switching to strain-electric field response of dielectrics.**

. *Journal of Advanced Dielectrics* vol. 3, (01). World Scientific Publishing.

## 2012

**Microwave dielectric properties of La<sub>3</sub>Ti<sub>2</sub>TaO<sub>11</sub> ceramics with perovskite-like layered structure.**

. *Journal of The European Ceramic Society* vol. 32, (16) 4015-4020.

**Toughening of zirconia/alumina composites by the addition of graphene platelets.**

. *Journal of The European Ceramic Society* vol. 32, (16) 4185-4193.

**Ferroelectric ceramics with enhanced remnant polarization by ordered coalescence of nano-crystals.**

. *Journal of Materials Chemistry* vol. 22, (44) 23547-23552.

**Reversibility in electric field-induced transitions and energy storage properties of bismuth-based perovskite ceramics.**

. *Journal of Physics D Applied Physics* vol. 45, (35).

**Spherical instrumented indentation of porous nanocrystalline zirconia.**

. *Journal of The European Ceramic Society* vol. 32, (1) 123-132.

**Phase stability and rapid consolidation of hydroxyapatite-zirconia nano-coprecipitates made using continuous hydrothermal flow synthesis.**

. *Journal of Biomaterials Applications* vol. 27, (1) 79-90.

**Analysis of femtosecond laser surface patterning on bulk single-crystalline diamond.**

. *Journal of Experimental Nanoscience* vol. 7, (6) 662-672.

**Kinetics of Densification and Grain Growth of Pure Tungsten During Spark Plasma Sintering.**

. *Metallurgical and Materials Transactions B-Process Metallurgy and Materials Processing Science* vol. 43, (6) 1608-1614.

## 2011

**Ferroelectric domain structures and electrical properties of fine-grained lead-free sodium potassium niobate ceramics.**

. *Journal of The American Ceramic Society* vol. 94, (10) 3391-3396.

**Magneto-electric properties of multiferroic  $\text{Pb}(\text{Zr}_{0.52}\text{Ti}_{0.48})\text{O}_3\text{-NiFe}_2\text{O}_4$  nanoceramic composites.**

. *Journal of The American Ceramic Society* vol. 94, (8) 2311-2314.

**High-strength nanograined and translucent hydroxyapatite monoliths via continuous hydrothermal synthesis and optimized spark plasma sintering.**

. *Acta Biomater* vol. 7, (2) 791-799.

**THE CONTRIBUTION OF ELECTRICAL CONDUCTIVITY, DIELECTRIC PERMITTIVITY AND DOMAIN SWITCHING IN FERROELECTRIC HYSTERESIS LOOPS.**

. *J. Adv Dielectrics* vol. 1, 107-118.

## 2010

**Effect of point defects on thermal depoling behavior of bismuth layer-structured ferroelectric ceramics.**

. *J Appl Phys* vol. 108, (9).

**Microstructure and electrical properties of Aurivillius phase  $(\text{CaBi}_2\text{Nb}_2\text{O}_9)_{(1-x)}(\text{BaBi}_2\text{Nb}_2\text{O}_9)_x$  solid solution.**

. *J Appl Phys* vol. 108, (1).

**Highly conductive low nickel content nano-composite dense cermets from nano-powders made via a continuous hydrothermal synthesis route.**

. *Solid State Ionics* vol. 181, (17-18) 827-834.

**The sintering and grain growth behaviour of ceramic-carbon nanotube nanocomposites.**

. *Compos Sci Technol* vol. 70, (6) 947-952.

**High temperature lead-free relaxor ferroelectric: Intergrowth Aurivillius phase  $\text{BaBi}_2\text{Nb}_2\text{O}_9\text{-Bi}_4\text{Ti}_3\text{O}_{12}$  ceramics.**

. *Journal of Applied Physics* vol. 107, (10).

**Piezoelectric Strontium Niobate and Calcium Niobate Ceramics with Super-High Curie Points.**

. *J Am Ceram Soc* vol. 93, (5) 1409-1413.

**Structural and chemical stability of multiwall carbon nanotubes in sintered ceramic nanocomposite.**

. *Adv Appl Ceram* vol. 109, (4) 240-245.

**Textured high Curie point piezoelectric ceramics prepared by spark plasma sintering.**

. *Adv Appl Ceram* vol. 109, (3) 139-142.

**Low temperature consolidated lead-free ferroelectric niobate ceramics with improved electrical properties.**

. *J Mater Res* vol. 25, (2) 240-247.

**Stability of Nanocrystalline Spark Plasma Sintered 3Y-TZP.**

. *Materials* vol. 3, (2) 800-814.

**Electrically conductive alumina-carbon nanocomposites prepared by Spark Plasma Sintering.**

. *Journal of The European Ceramic Society* vol. 30, (2) 153-157.

## 2009

### **Degradation resistance of 3Y-TZP ceramics sintered using spark plasma sintering.**

. *IOP Conference Series Materials Science and Engineering* vol. 5,.

### **Piezoelectric and Ferroelectric Properties of Bismuth Tungstate Ceramics Fabricated by Spark Plasma Sintering.**

. *J Am Ceram Soc* vol. 92, (12) 3108-3110.

### **Piezoelectric Ceramics with Super-High Curie Points.**

. *J Am Ceram Soc* vol. 92, (10) 2270-2275.

### **The grain size effect on the properties of Aurivillius phase Bi<sub>3.15</sub>Nd<sub>0.85</sub>Ti<sub>3</sub>O<sub>12</sub> ferroelectric ceramics.**

. *Nanotechnology* vol. 20, (38).

### **The grain size effect on the properties of Aurivillius phase Bi<sub>3.15</sub>Nd<sub>0.85</sub>Ti<sub>3</sub>O<sub>12</sub> ferroelectric ceramics.**

. *Nanotechnology* vol. 20, (38).

### **Fabrication and properties of dense ex situ magnesium diboride bulk material synthesized using spark plasma sintering.**

. *Supercond Sci Tech* vol. 22, (9).

### **The effect of Nd substitution on the electrical properties of Bi<sub>3</sub>NbTiO<sub>9</sub> Aurivillius phase ceramics.**

. *J Appl Phys* vol. 106, (4).

### **High-temperature ferroelectric phase transition observed in multiferroic Bi<sub>0.91</sub>La<sub>0.05</sub>Tb<sub>0.04</sub>FeO<sub>3</sub>.**

. *Applied Physics Letters* vol. 95, (1).

## 2008

### **Effect of a site substitution on the properties of CaBi<sub>2</sub>Nb<sub>2</sub>O<sub>9</sub> ferroelectric ceramics.**

. *Journal of The American Ceramic Society* vol. 91, (9) 2928-2932.

### **Dimethylformamide: an effective dispersant for making ceramic-carbon nanotube composites.**

. *Nanotechnology* vol. 19, (19).

### **Luminescence of Sr<sub>2</sub>SiO<sub>4-x</sub>N<sub>2x/3</sub> : Eu<sup>2+</sup> phosphors prepared by spark plasma sintering.**

. *J Electrochem Soc* vol. 155, (2) J58-J61.

## 2007

### **Dielectric, piezoelectric, and ferroelectric properties of grain-orientated Bi<sub>3.25</sub>La<sub>0.75</sub>Ti<sub>3</sub>O<sub>12</sub> ceramics.**

. *J Appl Phys* vol. 102, (10).

### **Effect of annealing on dielectric behavior and electrical conduction of W<sup>6+</sup> doped Bi<sub>3</sub>TiNbO<sub>9</sub> ceramics.**

. *Appl Phys Lett* vol. 90, (21).

## 2006

### **Lanthanum distribution and dielectric properties of Bi<sub>3-x</sub>La<sub>x</sub>TiNbO<sub>9</sub> bismuth layer-structured ceramics.**

. *Scripta Mater* vol. 55, (9) 791-794.

### **Effect of texture on dielectric properties and thermal depoling of Bi<sub>4</sub>Ti<sub>3</sub>O<sub>12</sub> ferroelectric ceramics.**

. *J Appl Phys* vol. 100, (7).

### **B-site donor and acceptor doped Aurivillius phase Bi<sub>3</sub>NbTiO<sub>9</sub> ceramics.**

. *J Eur Ceram Soc* vol. 26, (13) 2785-2792.

### **Dielectric relaxation of La<sup>3+</sup>-modified Bi<sub>3</sub>TiNbO<sub>9</sub> Aurivillius phase ceramics.**

. *J Am Ceram Soc* vol. 89, (9) 2939-2942.

**Orientation dependence of dielectric and relaxor behaviour in Aurivillius phase BaBi<sub>2</sub>Nb<sub>2</sub>O<sub>9</sub> ceramics prepared by spark plasma sintering.**

. *J Mater Sci-Mater El* vol. 17, (9) 657-661.

**Doping effects on the electrical conductivity of bismuth layered Bi<sub>3</sub>TiNbO<sub>9</sub>-based ceramics.**

. *J Appl Phys* vol. 100, (4).

**Structural and electrical properties of W<sup>6+</sup>-doped Bi<sub>3</sub>TiNbO<sub>9</sub> high-temperature piezoceramics.**

. *J Am Ceram Soc* vol. 89, (5) 1756-1760.

## 2005

**Thermal depoling of high Curie point Aurivillius phase ferroelectric ceramics.**

. *Appl Phys Lett* vol. 87, (8).

**A LeadFree HighCuriePoint Ferroelectric Ceramic, CaBi<sub>2</sub>Nb<sub>2</sub>O<sub>9</sub>.**

. *Cheminform* vol. 36, (28) no-no.Wiley.

**A lead-free high-Curie-point ferroelectric ceramic, CaBi<sub>2</sub>Nb<sub>2</sub>O<sub>9</sub>.**

. *Adv Mater* vol. 17, (10) 1261-+.

**Effective grain alignment in Bi<sub>4</sub>Ti<sub>3</sub>O<sub>12</sub> ceramics by superplastic-deformation-induced directional dynamic ripening.**

. *Adv Mater* vol. 17, (6) 676-+.

**Dielectric properties of single crystal diamond.**

. *Semicond Sci Tech* vol. 20, (3) 296-298.

## 2004

**The effect of (Li,Ce) and (K,Ce) doping in Aurivillius phase material CaBi<sub>4</sub>Ti<sub>4</sub>O<sub>15</sub>.**

. *Mater Res Bull* vol. 39, (9) 1237-1246.

**Grain orientation effects on the properties of a bismuth layer-structured ferroelectric (BLSF) Bi<sub>3</sub>NbTiO<sub>9</sub> solid solution.**

. *J Am Ceram Soc* vol. 87, (4) 602-605.

## 2003

**Preparation and electrical properties of bismuth layer-structured ceramic Bi<sub>3</sub>NbTiO<sub>9</sub> solid solution.**

. *Mater Res Bull* vol. 38, (2) 241-248.

## 2002

**Influence of sintering temperature on the properties of high T<sub>c</sub> bismuth layer structure ceramics.**

. *Mat Sci Eng B-Solid* vol. 88, (1) 62-67.

## 2001

**Formation of magnesium niobates in the MgO-Nb<sub>2</sub>O<sub>5</sub> system and the effects of Fe<sub>2</sub>O<sub>3</sub>.**

. *J Mater Sci Lett* vol. 20, (24) 2189-2191.

**Formation of columbite-type precursors in the mixture of MgO-Fe<sub>2</sub>O<sub>3</sub>-Nb<sub>2</sub>O<sub>5</sub> and the effects on fabrication of perovskites.**

. *Mater Lett* vol. 51, (6) 490-499.

**Effects of A-site (NaCe) substitution with Na-deficiency on structures and properties of CaBi<sub>4</sub>Ti<sub>4</sub>O<sub>15</sub>-based high- Curie-temperature ceramics.**

. *Jpn J Appl Phys 1* vol. 40, (11) 6501-6505.

**Effects of Cr<sub>2</sub>O<sub>3</sub> addition on the piezoelectric properties and microstructure of PbZr<sub>x</sub>Ti<sub>y</sub>(Mg<sub>1/3</sub>Nb<sub>2/3</sub>)(1-x-y)O-3 ceramics.**

. *J Eur Ceram Soc* vol. 21, (6) 703-709.

**Effects of processing routes on structures and dielectric properties of lead iron niobate-lead magnesium niobate binary system.**

. *Jpn J Appl Phys 1* vol. 40, (4A) 2348-2356.

**Effects of processing routes on structures and dielectric properties of lead iron niobate-lead magnesium niobate binary system.**

. *Japanese Journal of Applied Physics Part 1 Regular Papers and Short Notes and Review Papers* vol. 40, (4 A) 2348-2356.

2000

**A-Site (MCe) Substitution Effects on the Structures and Properties of CaBi<sub>4</sub>Ti<sub>4</sub>O<sub>15</sub> Ceramics.**

. *Japanese Journal of Applied Physics* vol. 39, (11R).IOP Publishing.

**Study on Low Frequency Internal Friction for Pb(Zr,Ti)O<sub>3</sub> Ferroelectric Ceramics.**

. *Physica Status Solidi (a) Applications and Materials Science* vol. 179, (1) 275-283.Wiley.

**Anomalous internal friction in lead metaniobate ceramics.**

. *Journal of Applied Physics* vol. 87, (6) 3186-3188.Aip Publishing.

**Low-frequency internal friction study on modified lead metaniobate ceramics.**

. *Chinese Physics B* vol. 9, (2) 149-152.IOP Publishing.