

Dr Haixue Yan

PhD, PGCAP, CEng, FIMMM and FRSC

School of Engineering and Materials Science
Queen Mary University of London
Mile End Road
London E1 4NS

tel: +44 (0)20 7882 5164

email: h.x.yan@qmul.ac.uk web: www.sems.qmul.ac.uk/h.x.yan

2026

Enhanced piezoelectric properties of Pb(Ni_{1/3}Nb_{2/3})O₃ - Pb(Yb_{1/2}Nb_{1/2})O₃ - Pb(Zr,Ti)O₃ ceramics by the design of multiphase coexistence.

. *Journal of The European Ceramic Society* vol. 46, (5).Elsevier.

Grain Size-Dependent Defect and Domain Evolution in Lead Titanate-Based Relaxor Ferroelectrics.

. *Acs Applied Materials & Interfaces* vol. 18, (17) 24889-24898.American Chemical Society (Acs).

Flexible ultrasound sensor based on ErPMNPT ceramics for vascular monitoring.

. *IEEE Sensors Journal* vol. PP, (99) 1-1.Institute of Electrical and Electronics Engineers (IEEE).

Structural Origin of Morphotropic Phase Boundary in Advanced Perovskite Ferroelectric Oxides.

. *Journal of The American Chemical Society*.American Chemical Society (Acs).

Susceptible Antiferroelectric/Ferroelectric Transitions in Silver Niobate-Based Ceramics Induced by Manual Mechanical Processing.

. *Inorganic Chemistry* vol. 65, (6) 3215-3224.American Chemical Society (Acs).

2025

Strategic optimization of polar nanoregions for superior dielectric tunability in PMNPT-based ceramics.

. *Journal of The European Ceramic Society* vol. 45, (16).Elsevier.

Dynamic Atomistic Polar Structure Underpins Ultrahigh Linear Electro-Optic Coefficient in Transparent Ferroelectric Ceramics.

. *Journal of The American Chemical Society*.American Chemical Society (Acs).

Lead-free piezoelectric ceramics with ultralow mechanical quality factor.

. *Materials Research Bulletin* vol. 191,.Elsevier.

Engineering polar nanoclusters for enhanced microwave tunability in ferroelectric thin films.

. *Nature Communications* vol. 16, (1).Springer Nature.

High entropy engineered polymer blends with enhanced dielectric properties and high temperature stability.

. *Nature Communications* vol. 16, (1).Springer Nature.

Review of enhancing thermal conductivity in polymer-based dielectrics as passive components.

. *Progress in Polymer Science* vol. 169,.Elsevier.

Boosting the electrocaloric effect with broad working temperature span in lead-free relaxor ferroelectrics through disorder modulation.

. *Applied Physics Letters* vol. 127, (12).Aip Publishing.

Lead-Free (1-x)Ba(Zr_{0.2}Ti_{0.8})O₃-x(Ba_{0.7}Ca_{0.3})TiO₃Based Ferroelectrics with Diffuse Phase Transitions for Sustainable Electrocaloric Applications.

. *The Journal of Physical Chemistry C* vol. 129, (38) 17229-17235.American Chemical Society (Acs).

Effect of Samarium Doping on the Energy Storage Properties of Bismuth Sodium Titanate-Based Lead-Free Ceramics.

. *Acs Applied Materials & Interfaces* vol. 17, (38) 53780-53790. American Chemical Society (Acs).

Relationships between structure and properties in commercial lead zirconate titanate (PZT) piezoceramics.

. *Journal of Materiomics* vol. 11, (5). Elsevier.

Direct magnetoelectric coupling from magnetically/ferroelectrically active cation in low-symmetry octahedron.

. *Physical Review B* vol. 112, (5). American Physical Society (Aps).

Tunable and anomalous electrocaloric behaviors in Bi_{0.5}Na_{0.5}TiO₃-based relaxor enabled by dynamics of polar nanoregions.

. *Acta Materialia* vol. 293, Elsevier.

Phase Transitions in Bi/Ca Modified AgNbO₃ Ceramics with Excellent Energy Storage Density and Storage Intensity.

. *Small* vol. 21, (32). Wiley.

Enhanced electrocaloric effect in lead-free relaxor ferroelectrics via point defect engineering.

. *Applied Physics Letters* vol. 126, (23). Aip Publishing.

Dislocation-nanoparticle interactions in TiB₂p/Cu composites based on molecular dynamics and experiments.

. *Journal of Alloys and Compounds* vol. 1033, Elsevier.

Low cost small scale recycling aluminium cans for energy conservation and environmental sustainability.

. *Environmental Technology* vol. 46, (22) 4575-4582. Taylor & Francis.

Boosting energy density by frustration.

. *Science China Materials* vol. 68, (6) 2148-2149. Springer Nature.

Unveiling the mechanism of substitution-induced high piezoelectric performance in PLZT ceramics.

. *Journal of Advanced Ceramics*. Tsinghua University Press.

Phase transformation in lead titanate based relaxor ferroelectrics with ultra-high strain.

. *Nature Communications* vol. 16, (1). Springer Nature.

Investigation of electric field-induced phase transitions in unfilled tungsten bronze relaxor ceramics designed by the high entropy concept.

. *Acta Materialia* vol. 284, Elsevier.

Healing filler/matrix interfaces in drawn BN/UHMWPE composites by a simple thermal annealing treatment.

. *Rsc Applied Polymers* vol. 3, (2) 361-369. Royal Society of Chemistry (Rsc).

Optimization of Thermoelectric Transport Properties in Nanocomposite MgAgSb-Based Alloys.

. *Journal of Inorganic Materials*. Shanghai Institute of Ceramics.

Non-volatile voltage-controlled magnetization in single-phase multiferroic ceramics at room temperature.

. *Journal of Materiomics* vol. 11, (1). Elsevier.

2024

Ferroelectric anomaly of perovskite layer structured Pb²⁺-doped Sr₂Nb₂O₇ ceramics.

. *Journal of The American Ceramic Society* vol. 107, (6) 3989-3999.

Processing and characterisation of hot rolling pressed PVDF films with enhanced field-induced polarisation.

. *Polymer* vol. 302,.

High Thermoelectric Performance Related to PVDF Ferroelectric Domains in P-Type Flexible PVDF-Bi_{0.5}Sb_{1.5}Te₃ Composite Film.

. *Small* vol. 20, (19).

Dielectric probing of low-temperature degradation resistance of commercial zirconia bio-ceramics.
. *Dental Materials* vol. 40, (6) 921-929.Elsevier.

Dielectric relaxation and conductivity phenomena in ferroelectric ceramics at high temperatures.
. *Journal of The European Ceramic Society* vol. 44, (5) 2886-2902.

Microwave tunability in tin substituted barium titanate.
. *Journal of The European Ceramic Society* vol. 44, (3) 1627-1635.Elsevier.

Origin of Polarization in Bismuth Sodium Titanate-Based Ceramics.
. *Journal of The American Chemical Society* vol. 146, (8) 5569-5579.American Chemical Society (Acs).

High-temperature dielectric polymer composite for high power energy storage applications.
. *Science China Chemistry* vol. 67, (8) 2425-2426.Springer Nature.

Microstructure evolution and the deformation mechanism in nanocrystalline superior-deformed tantalum.
. *Nanoscale* vol. 16, (9) 4826-4840.Royal Society of Chemistry (Rsc).

2023

Structure and dielectric properties in Mg/Nb co-substituted bismuth sodium titanate.
. *Journal of Alloys and Compounds* vol. 969,.Elsevier.

Energy storage properties of samarium-doped bismuth sodium titanate-based lead-free ceramics.
. *Chemical Engineering Journal* vol. 473,.

BROADBAND DIELECTRIC CHARACTERIZATION OF CARBON BLACKREINFORCED NATURAL RUBBER.
. *Rubber Chemistry and Technology* vol. 96, (4) 656-666.Rubber Division, Acs.

Fundamentals, advances and perspectives of piezocatalysis: A marriage of solid-state physics and catalytic chemistry.
. *Progress in Materials Science* vol. 138,.

Microwave characterization of two Ba 0.6 Sr 0.4 TiO 3 dielectric thin films with out-of-plane and in-plane electrode structures.
. *Journal of Advanced Ceramics* vol. 12, (8) 1521-1532.Tsinghua University Press.

Structure and Conductivity in LISICON Analogues within the Li₄GeO₄Li₂MoO₄ System.
. *Inorganic Chemistry* vol. 62, (30) 11876-11886.American Chemical Society (Acs).

Simultaneous Increase in Dielectric Breakdown Strength and Thermal Conductivity of Oriented UHMWPE Containing Diamond Nanoparticles.
. *Macromolecules* vol. 56, (20) 8183-8191.American Chemical Society (Acs).

Enhanced piezoelectricity in Na and Ce co-doped CaBi₄Ti₄O₁₅ ceramics for high-temperature applications.
. *Journal of Advanced Ceramics* vol. 12, (7) 1331-1344.

Structural evolution and coexistence of ferroelectricity and antiferromagnetism in Fe, Nb co-doped BaTiO₃ ceramics.
. *Journal of The European Ceramic Society* vol. 43, (6) 2460-2468.Elsevier.

High-entropy MTiO₃ perovskite oxides with glass-like thermal conductivity for thermoelectric applications.
. *Journal of Alloys and Compounds* vol. 937,.Elsevier.

Magnetolectric coupling at microwave frequencies observed in bismuth ferrite-based multiferroics at room temperature.
. *Journal of Material Science and Technology* vol. 137, 100-103.Elsevier.

Achieving Ultrahigh Energy Storage Density of La and Ta Codoped AgNbO₃ Ceramics by Optimizing the Field-Induced Phase Transitions.
. *Acs Applied Materials & Interfaces* vol. 15, (3) 4246-4256.American Chemical Society (Acs).

Effect of Ag⁺ doping and Ag addition on the thermoelectric properties of KSr₂Nb₅O₁₅.

. *Ceramics International* vol. 49, (2) 1731-1741.Elsevier.

Deciphering the peculiar hysteresis loops of 0.05Pb(Mn_{1/3}Sb_{2/3})O₃0.95Pb(Zr_{0.52}Ti_{0.48})O₃ piezoelectric ceramics.

. *Acta Materialia* vol. 244,.Elsevier.

Origin of the switchable photocurrent direction in BiFeO₃ thin films.

. *Materials Horizons* vol. 10, (12) 5892-5897.Royal Society of Chemistry (Rsc).

2022

Local Structure in BIMEVOXes (ME = Ge, Sn).

. *Chemistry of Materials* vol. 35, (1) 189-206.American Chemical Society (Acs).

Antiferroelectric-like Behavior in a Lead-Free Perovskite Layered Structure Ceramic.

. *Inorganic Chemistry* vol. 61, (50) 20316-20325.American Chemical Society (Acs).

Grain orientation evolution and multi-scale interfaces enhanced thermoelectric properties of textured Sr_{0.9}La_{0.1}TiO₃ based ceramics.

. *Journal of The European Ceramic Society* vol. 42, (15) 7017-7026.Elsevier.

In-situ growth of carbon nanotubes on ZnO to enhance thermoelectric and mechanical properties.

. *Journal of Advanced Ceramics* vol. 11, (12) 1932-1943.Tsinghua University Press.

Stability of 3Y-TZP nano zirconia powder after hydrothermal ageing treatment.

. *Advances in Applied Ceramics* vol. 121, (5-8) 159-165.Sage Publications.

Terahertz Faraday Rotation of SrFe₁₂O₁₉Hexaferrites Enhanced by Nb Doping.

. *Acs Applied Materials and Interfaces* vol. 14, (41) 46738-46747.

Dielectric polymer composites with ultra-high thermal conductivity and low dielectric loss.

. *Composites Science and Technology* vol. 229,.Elsevier.

Effect of composition on the dielectric properties and thermal conductivity of -SiAlON ceramics.

. *Journal of Materials Science: Materials in Electronics* vol. 33, (28) 22480-22491.Springer Nature.

Low thermal conductivity in A-site high entropy perovskite relaxor ferroelectric.

. *Applied Physics Letters* vol. 121, (11).Aip Publishing.

Enhancement of Thermoelectric Performance in Bi_{0.5}Sb_{1.5}Te₃ Particulate Composites Including Ferroelectric BaTiO₃ Nanodots.

. *Acs Applied Materials & Interfaces* vol. 14, (32) 37204-37212.American Chemical Society (Acs).

A novel high-entropy perovskite ceramics Sr_{0.9}La_{0.1}(Zr_{0.25}Sn_{0.25}Ti_{0.25}Hf_{0.25})O₃ with low thermal conductivity and high Seebeck coefficient.

. *Journal of The European Ceramic Society* vol. 42, (8) 3480-3488.Elsevier.

Temperature dependence in ageing process in commercial zirconia dental ceramics.

. *Advances in Applied Ceramics* vol. 121, (4) 150-153.Sage Publications.

Low-cost Free-standing ferroelectric polymer films with high polarization produced via pressing-and-folding.

. *Journal of Materiomics* vol. 8, (3) 640-648.Elsevier.

Effect of La³⁺, Ag⁺ and Bi³⁺ doping on thermoelectric properties of SrTiO₃: First-principles investigation.

. *Ceramics International* vol. 48, (10) 13803-13816.Elsevier.

Chemical Solution Deposition of SinglePhase BiFeO₃ Thin Films on Transparent Substrates.

. *Solar Rrl* vol. 6, (7).Wiley.

Phase transformations in an Aurivillius layer structured ferroelectric designed using the high entropy concept.

. *Acta Materialia* 117815-117815.Elsevier.

Enhanced energy storage performance under low electric field in Sm³⁺ doped AgNbO₃ ceramics.

. *Journal of Materiomics* vol. 8, (2) 266-273.Elsevier.

Reduced lattice thermal conductivity of perovskite-type high-entropy (Ca_{0.25}Sr_{0.25}Ba_{0.25}RE_{0.25})TiO₃ ceramics by phonon engineering for thermoelectric applications.

. *Journal of Alloys and Compounds* vol. 898,.Elsevier.

Local Structure and Conductivity in the BIGAVOX System.

. *The Journal of Physical Chemistry C* vol. 126, (4) 2108-2120.American Chemical Society (Acs).

Temperature-dependent deformation in silver-particle-covered copper nanowires by molecular dynamics simulation.

. *Journal of Materiomics* vol. 8, (1) 68-78.Elsevier.

Exploration about superior anti-counterfeiting ability of Sm³⁺ doped K₂Sr₂Nb₅O₁₅ photochromic ceramics: Origin and atomic-scale mechanism.

. *Journal of Materiomics* vol. 8, (1) 38-46.Elsevier.

High-entropy (Ca_{0.2}Sr_{0.2}Ba_{0.2}La_{0.2}Pb_{0.2})TiO₃ perovskite ceramics with A-site short-range disorder for thermoelectric applications.

. *Journal of Material Science and Technology* vol. 97, 182-189.Elsevier.

Local structure in a tetravalent-substituent BIMEVOX system: BIGEVOX.

. *Journal of Materials Chemistry A* vol. 10, (7) 3793-3807.Royal Society of Chemistry (Rsc).

Ultra-high energy density integrated polymer dielectric capacitors.

. *Journal of Materials Chemistry A* vol. 10, (18) 10171-10180.Royal Society of Chemistry (Rsc).

Silver niobate perovskites: structure, properties and multifunctional applications.

. *Journal of Materials Chemistry A* vol. 10, (28) 14747-14787.Royal Society of Chemistry (Rsc).

2021

Grain Size Effects in Mn-Modified 0.67BiFeO₃0.33BaTiO₃ Ceramics.

. *Acs Applied Materials & Interfaces* vol. 13, (48) 57548-57559.American Chemical Society (Acs).

Terahertz Characterization of Lead-Free Dielectrics for Different Applications.

. *Acs Applied Materials & Interfaces* vol. 13, (45) 53492-53503.American Chemical Society (Acs).

Terahertz probing of low temperature degradation in zirconia bioceramics.

. *Journal of The American Ceramic Society*.

Facile one-step synthesis and enhanced photocatalytic activity of WC/ferroelectric nanocomposite.

. *Journal of Materials Chemistry A*.Royal Society of Chemistry (Rsc).

Characterization of microwave and terahertz dielectric properties of single crystal La₂Ti₂O₇ along one single direction.

. *Journal of The European Ceramic Society*.

Cationic polymer brush-coated bioglass nanoparticles for the design of bioresorbable RNA delivery vectors.

. *European Polymer Journal* vol. 156,.Elsevier.

Electric field-induced transformations in bismuth sodium titanate-based materials.

. *Progress in Materials Science* vol. 122,.Elsevier.

Structural Evolution in BiNbO₄.

. *Inorganic Chemistry: Including Bioinorganic Chemistry*.American Chemical Society.

Terahertz Reading of Ferroelectric Domain Wall Dielectric Switching.

. *Acs Applied Materials & Interfaces*.American Chemical Society (Acs).

Grain orientation evolution and thermoelectric properties of textured (Ca_{0.87}Ag_{0.1}La_{0.03})₃Co₄O₉ ceramics prepared by tape casting.

. *Ceramics International* vol. 47, (6) 8365-8374.Elsevier.

Investigation of transitions between the M-phases in AgNbO₃ based ceramics.

. *Journal of Materials Chemistry A*.Royal Society of Chemistry.

Effect of processing on the structures and properties of bismuth sodium titanate compounds.

. *Journal of Materials Research* 1-11.Springer.

Multi elements substituted Aurivillius phase relaxor ferroelectrics using high entropy design concept.

. *Materials and Design* 109447-109447.Elsevier.

Response to comment on point defect structure of La-doped SrTiO₃ ceramics with colossal permittivity.

. *Scripta Materialia* vol. 190, 118-120.

Tunable phase transitions in NaNbO₃ ceramics through bismuth/vacancy modification.

. *Journal of Materials Chemistry C* vol. 9, (12) 4289-4299.Royal Society of Chemistry (Rsc).

2020

Temperature-dependent deformation processes in two-phase TiAl+Ti₃Al nano-polycrystalline alloys.

. *Materials & Design* vol. 199, 109422-109422.

Ultrafast Electric Field-Induced Phase Transition in Bulk Bi_{0.5}Na_{0.5}TiO₃ under High-Intensity Terahertz Irradiation.

. *Acs Photonics*.American Chemical Society.

Perovskite Bi_{0.5}Na_{0.5}TiO₃-based materials for dielectric capacitors with ultrahigh thermal stability.

. *Materials and Design* 109344-109344.Elsevier.

High Tunability and Low Loss in Layered Perovskite Dielectrics through Intrinsic Elimination of Oxygen Vacancies.

. *Chemistry of Materials*.American Chemical Society (Acs).

Low-loss High Entropy Relaxor-like Ferroelectrics with A-site Disorder.

. *Journal of The European Ceramic Society*.Elsevier.

Structure and dielectric properties of double A-site doped bismuth sodium titanate relaxor ferroelectrics for high power energy storage applications.

. *Journal of Materials Chemistry A*.Royal Society of Chemistry.

Multiscale understanding of electric polarization in poly(vinylidene fluoride)-based ferroelectric polymers.

. *Journal of Materials Chemistry C*.Royal Society of Chemistry.

Phase transitions in RbPrNb₂O₇, a layer structured ferroelectric with a high Curie point.

. *Acta Materialia* vol. 200, 971-979.Elsevier.

Polar nano-clusters in nominally paraelectric ceramics demonstrating high microwave tunability for wireless communication.

. *Journal of The European Ceramic Society* vol. 40, (12) 3996-4003.Elsevier.

Enhanced dielectric properties of highly dense Ba_{0.5}Sr_{0.5}TiO₃ ceramics via non-toxic gelcasting.

. *Journal of Materials Science: Materials in Electronics* vol. 31, (20) 17819-17827.Springer Nature.

Publisher's Note: Room-temperature multiferroic behavior in layer-structured Aurivillius phase ceramics [Appl. Phys Lett. 117, 052903 (2020)].

. *Applied Physics Letters* vol. 117, (9).Aip Publishing.

Solution-Processed Epitaxial Growth of Arbitrary Surface Nanopatterns on Hybrid Perovskite Monocrystalline Thin Films.

. *Acs Nano* vol. 14, (9) 11029-11039.American Chemical Society (Acs).

Room-temperature multiferroic behavior in layer-structured Aurivillius phase ceramics.

. *Applied Physics Letters* vol. 117, (5) 052903-052903. Aip Publishing.

Ultrahigh field-induced strain in lead-free ceramics.

. *Nano Energy* 105037-105037. Elsevier.

Giant energy storage density in PVDF with internal stress engineered polar nanostructures.

. *Nano Energy* vol. 72, Elsevier.

Cobalt-induced structural modulation in multiferroic Aurivillius-phase oxides.

. *Journal of Materials Chemistry C. Royal Society of Chemistry (Rsc)*.

Colossal thermoelectric enhancement in $\text{Cu}_{2+x}\text{Zn}_1\text{Sn}_4$ solid solution by local disordering of crystal lattice and multi-scale defect engineering.

. *Journal of Materials Chemistry A* vol. 8, (21) 10909-10916. Royal Society of Chemistry.

High Thermoelectric Performance in SnTe Nanocomposites with All-Scale Hierarchical Structures.

. *Acs Applied Materials and Interfaces. American Chemical Society*.

Boosting the Thermoelectric Performance of Calcium Cobaltite Composites through Structural Defect Engineering.

. *Acs Applied Materials & Interfaces* vol. 12, (19) 21623-21632. American Chemical Society (Acs).

The Contribution of Electrical Conductivity, Dielectric Permittivity and Domain Switching in Ferroelectric Hysteresis Loops.

. *Progress in Advanced Dielectrics 1-20. World Scientific Publishing*.

Ferroelectrics: Terahertz Probing Irreversible Phase Transitions Related to Polar Clusters in $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ Based Ferroelectric (Adv. Electron. Mater. 4/2020).

. *Advanced Electronic Materials* vol. 6, (4). Wiley.

Terahertz Probing Irreversible Phase Transitions Related to Polar Clusters in $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ Based Ferroelectric.

. *Advanced Electronic Materials* 1901373-1901373. Wiley.

Interactive human-machine learning framework for modelling of ferroelectric dielectric composites.

. *Journal of Materials Chemistry C* vol. 8, (30) 10352-10361. Royal Society of Chemistry (Rsc).

Domain Wall Free Polar Structure Enhanced Photodegradation Activity in Nanoscale Ferroelectric $\text{Ba}_x\text{Sr}_{1-x}\text{TiO}_3$.

. *Advanced Energy Materials* vol. 10, (38).

2019

Microstructure and thermoelectric performance of $\text{La}_{0.9}\text{Ag}_{0.1}\text{Co}_4\text{O}_9$ /nanosized Ag composite ceramics.

. *International Journal of Ceramic Engineering & Science* vol. 2, (1) 7-16. Wiley.

Dielectric and ferroelectric properties of BTFCO thin films.

. *Journal of Electroceramics* vol. 43, (1-4) 92-95. Springer Nature.

Ultrahigh -phase content poly(vinylidene fluoride) with relaxor-like ferroelectricity for high energy density capacitors.

. *Nature Communications* vol. 10, (1). Springer Nature.

Isolation of a ferroelectric intermediate phase in antiferroelectric dense sodium niobate ceramics.

. *Acta Materialia* vol. 179, 255-261. Elsevier Bv.

Relaxor behavior and photocatalytic properties of $\text{BaBi}_2\text{Nb}_2\text{O}_9$.

. *Journal of The American Ceramic Society. Wiley*.

Symmetry-mode analysis for intuitive observation of structure-property relationships in the lead-free antiferroelectric (1-x)AgNbO₃xLiTaO₃.

. *Iucrj* vol. 6, (Pt 4) 740-750. *International Union of Crystallography (Iucr)*.

Multiferroic properties of single phase Bi₃NbTiO₉ based textured ceramics.

. *Journal of Alloys and Compounds* vol. 788, 701-704.

Spark plasma sintering of grain-oriented Sr₂Bi₄Ti₅O₁₈ aurivillius phase ceramics.

. *Journal of Alloys and Compounds* vol. 782, 6-9.

Orthoenstatite to forsterite phase transformation in magnesium germanate ceramics.

. *Ceramics International* vol. 45, (6) 7878-7884.

Microstructure and broadband dielectric properties of Zn₂SiO₄ ceramics with nano-sized TiO₂ addition.

. *Ceramics International*.

Twostep processing of thermoelectric (Ca_{0.9}Ag_{0.1})₃Co₄O₉/nanosized Ag composites with high ZT.

. *Journal of The European Ceramic Society*.

Remarkably enhanced polarisability and breakdown strength in PVDF-based interactive polymer blends for advanced energy storage applications.

. *Polymer* vol. 168, 246-254.

Point defect structure of La-doped SrTiO₃ ceramics with colossal permittivity.

. *Acta Materialia* vol. 164, 76-89. *Elsevier*.

On the origin of grain size effects in Ba(Ti_{0.96}Sn_{0.04})O₃ perovskite ceramics.

. *Journal of The European Ceramic Society*.

Phase transitions in tantalum-modified silver niobate ceramics for high power energy storage.

. *Journal of Materials Chemistry A* vol. 7, (2) 834-842.

Bi₂Fe₄O₉ thin films as novel visible-light-active photoanodes for solar water splitting.

. *Journal of Materials Chemistry A* vol. 7, (16) 9537-9541. *Royal Society of Chemistry (Rsc)*.

Silver niobate based lead-free ceramics with high energy storage density.

. *Journal of Materials Chemistry A* vol. 7, (17) 10702-10711. *Royal Society of Chemistry (Rsc)*.

2018

Crystal structure and electrical properties of textured Ba₂Bi₄Ti₅O₁₈ ceramics.

. *Journal of The European Ceramic Society*.

Enhanced piezoelectric properties and electrocaloric effect in novel lead-free (Bi_{0.5}K_{0.5})TiO₃-La(Mg_{0.5}Ti_{0.5})O₃ ceramics.

. *Journal of The American Ceramic Society* vol. 101, (12) 5503-5513.

Preparation and mechanical performance of graphene platelet reinforced titanium nanocomposites for high temperature applications.

. *Journal of Alloys and Compounds* vol. 765, 1111-1118.

Microstructure characterization and thermoelectric properties of Sr_{0.9}La_{0.1}TiO₃ ceramics with nano-sized Ag as additive.

. *Journal of Alloys and Compounds* vol. 762, 80-89.

Enhanced thermoelectric performance of Sn-doped Cu₃SbS₄.

. *Journal of Materials Chemistry C* vol. 6, (31) 8546-8552.

Electric-field-induced local distortion and large electrostrictive effects in lead-free NBT-based relaxor ferroelectrics.

. *Journal of The European Ceramic Society*.

Crystal Chemistry and Magnetic Properties of Gd-Substituted Aurivillius-Type Bi₅FeTi₃O₁₅ Ceramics.
. *Journal of Physical Chemistry C* vol. 122, (27) 15733-15743.

Perovskite Sr_x(Bi_{1-x}Na_{0.97x}Li_{0.03})_{0.5}TiO₃ ceramics with polar nano regions for high power energy storage.
. *Nano Energy* vol. 50, 723-732.

SrFe₂O₁₉ based ceramics with ultra-low dielectric loss in the millimetre-wave band.
. *Applied Physics Letters* vol. 112, (14). Aip Publishing.

Bi_{3.25}La_{0.75}Ti_{2.5}Nb_{0.25}(Fe_{0.5}Co_{0.5})_{0.25}O₁₂, a single phase room temperature multiferroic.
. *Journal of Materials Chemistry C* vol. 6, (11) 2733-2740.

Enhanced dielectric tunability and energy storage properties of plate-like Ba_{0.6}Sr_{0.4}TiO₃/poly(vinylidene fluoride) composites through texture arrangement.
. *Composites Science and Technology* vol. 158, 112-120.

2017

Giant electrostrain accompanying structural evolution in lead-free NBT-based piezoceramics.
. *Journal of Materials Chemistry C* vol. 6, (4) 814-822.

Phase evolution and electrical behaviour of samarium-substituted bismuth ferrite ceramics.
. *Journal of The European Ceramic Society*.

Phase composition and temperature dependence of electrocaloric effect in leadfree Bi_{0.5}Na_{0.5}TiO₃BaTiO₃(Sr_{0.7}Bi_{0.20.1})TiO₃ ceramics.
. *Journal of The European Ceramic Society* vol. 37, (15) 4732-4740. Elsevier.

Ordered coalescence of nano-crystals in alkaline niobate ceramics with high remanent polarization.
. *Journal of Materiomics* vol. 3, (4) 267-272.

Phase transitions in bismuth-modified silver niobate ceramics for high power energy storage.
. *Journal of Materials Chemistry A* vol. 5, (33) 17525-17531.

Titanium Dioxide Engineered for Near-dispersionless High Terahertz Permittivity and Ultra-low-loss.
. *Scientific Reports* vol. 7, (1). Springer Nature.

Type I pseudofirstorder phase transition induced electrocaloric effect in leadfree Bi_{0.5}Na_{0.5}TiO₃0.06BaTiO₃ ceramics.
. *Applied Physics Letters* vol. 110, (18). Aip Publishing.

Microstructural comparison of effects of hafnium and titanium additions in spark-plasma-sintered Fe-based oxide-dispersion strengthened alloys.
. *Journal of Nuclear Materials* vol. 487, 433-442. Elsevier.

Effect of Phase Transitions on Thermal Depoling in Lead-Free 0.94(Bi_{0.5}Na_{0.5}TiO₃)_{0.06}(BaTiO₃) Based Piezoelectrics.
. *The Journal of Physical Chemistry C* vol. 121, (10) 5709-5718. American Chemical Society (Acs).

Terbium-induced phase transitions and weak ferromagnetism in multiferroic bismuth ferrite ceramics.
. *Journal of Materials Chemistry C* vol. 5, (10) 2669-2685. Royal Society of Chemistry (Rsc).

Topochemical transformation of two-dimensional single crystalline Na_{0.5}Bi_{0.5}TiO₃BaTiO₃ platelets from Na_{0.5}Bi_{4.5}Ti₄O₁₅ precursors and their piezoelectricity.
. *Journal of Materials Chemistry A* vol. 5, (30) 15780-15788. Royal Society of Chemistry (Rsc).

2016

Theory-Guided Synthesis of an Eco-Friendly and Low-Cost Copper Based Sulfide Thermoelectric Material.
. *The Journal of Physical Chemistry C* vol. 120, (48) 27135-27140. American Chemical Society (Acs).

Carriers concentration tailoring and phonon scattering from n-type zinc oxide (ZnO) nanoinclusion in p- and n-type bismuth telluride (Bi₂Te₃): Leading to ultra low thermal conductivity and excellent thermoelectric properties.

. *Journal of Alloys and Compounds* vol. 694, 864-868.

Lead free Bi₃TaTiO₉ ferroelectric ceramics with high Curie point.

. *Materials Letters* vol. 175, 79-81. Elsevier.

Tuning the electrocaloric enhancement near the morphotropic phase boundary in lead-free ceramics.

. *Scientific Reports* vol. 6, (1). Springer Nature.

Strain-Dependent Dielectric Behavior of Carbon Black Reinforced Natural Rubber.

. *Macromolecules* vol. 49, (6) 2339-2347. American Chemical Society (Acs).

Efficacy of lone-pair electrons to engender ultralow thermal conductivity.

. *Scripta Materialia* vol. 111, 49-53.

Room temperature magnetoelectric coupling in intrinsic multiferroic Aurivillius phase textured ceramics.

. *Dalton Transactions* vol. 45, (36) 14049-14052. Royal Society of Chemistry (Rsc).

Growth of SiC platelets using contactless flash technique.

. *Journal of The Ceramic Society of Japan* vol. 124, (9) 845-847. Ceramic Society of Japan.

High energy density in silver niobate ceramics.

. *Journal of Materials Chemistry A* vol. 4, (44) 17279-17287. Royal Society of Chemistry (Rsc).

2015

Crystallographic Structure and Ferroelectricity of (AxLa_{1-x})₂Ti₂O₇ (A = Sm and Eu) Solid Solutions with High T_c.

. *Journal of The American Ceramic Society* vol. 99, (2) 523-530. Wiley.

A High Curie Point Ferroelectric Ceramic Ca₃(VO₄)₂.

. *Ferroelectrics* vol. 487, (1) 94-100. Taylor & Francis.

Processing and microstructure characterisation of oxide dispersion strengthened Fe₁₄Cr_{0.4}Ti_{0.25}Y₂O₃ ferritic steels fabricated by spark plasma sintering.

. *Journal of Nuclear Materials* vol. 464, 61-68. Elsevier.

Role of synthesis method on microstructure and mechanical properties of graphene/carbon nanotube toughened Al₂O₃ nanocomposites.

. *Ceramics International* vol. 41, (8) 9813-9822.

Dielectric relaxation and electrical conductivity in Ca₅Nb₄TiO₁₇ ceramics.

. *Ceramics International* vol. 41, (8) 9923-9930.

Unfolding grain size effects in barium titanate ferroelectric ceramics.

. *Scientific Reports* vol. 5, (1). Springer Nature.

Effect of Ca substitution sites on dielectric properties and relaxor behavior of Ca doped barium strontium titanate ceramics.

. *Journal of Materials Science Materials in Electronics* vol. 26, (4) 2486-2492.

Study on properties of tantalum-doped La₂Ti₂O₇ ferroelectric ceramics.

. *Journal of Advanced Dielectrics* vol. 5, (01). World Scientific Publishing.

Reduced thermal conductivity by nanoscale intergrowths in perovskite like layered structure La₂Ti₂O₇.

. *Journal of Applied Physics* vol. 117, (7). Aip Publishing.

Microwave and terahertz dielectric properties of MgTiO₃-CaTiO₃ ceramics.

. *Materials Letters* vol. 138, 225-227.

Ferroelectricity in DionJacobson ABiNb₂O₇ (A = Rb, Cs) compounds.

. *Journal of Materials Chemistry C* vol. 3, (1) 19-22. Royal Society of Chemistry (Rsc).

Enhancement of electric field-induced strain in BaTiO₃ ceramics through grain size optimization.

. *Physica Status Solidi (a) Applications and Materials Science* vol. 212, (2) 433-438.

Effect of different templates on structure evolution and large strain response under a low electric field in -textured lead-free BNT-based piezoelectric ceramics.

. *Journal of The European Ceramic Society* vol. 35, (9) 2489-2499.

2014

Ferroelectric and dielectric properties of Nd_{2x}CexTi₂O₇ ceramics.

. *Advances in Applied Ceramics* vol. 114, (4) 191-197. Sage Publications.

Low Temperature Magnetic and Dielectric Anomalies in Rare Earth Substituted BiFeO₃ Ceramics.

. *Journal of The American Ceramic Society* vol. 97, (12) 3729-3732. Wiley.

Short range polar state transitions and deviation from Rayleigh-type behaviour in Bi_{0.5}Na_{0.5}TiO₃-based perovskites.

. *Applied Physics Letters* vol. 105, (10).

Three Layer Perovskite Like Structured Pr₃Ti₂TaO₁₁ Ferroelectrics with Super High Curie Point.

. *Journal of The American Ceramic Society* vol. 97, (11) 3624-3630. Wiley.

Spark plasma sintering of alumina composites with graphene platelets and silicon carbide nanoparticles.

. *Advanced Engineering Materials* vol. 16, (9) 1111-1118.

Enhancement of thermoelectric properties by atomic-scale percolation in digenite Cu_xS.

. *Journal of Materials Chemistry A* vol. 2, (25) 9486-9489.

Large ZT enhancement in hot forged nanostructured p-type Bi_{0.5}Sb_{1.5}Te₃ bulk alloys.

. *Journal of Materials Chemistry A* vol. 2, (16) 5785-5790.

Lithium-induced phase transitions in lead-free Bi_{0.5}Na_{0.5}TiO₃ based ceramics.

. *Journal of Physical Chemistry C* vol. 118, (16) 8564-8570.

Effect of dysprosium substitution on crystal structure and physical properties of multiferroic BiFeO₃ ceramics.

. *Journal of The European Ceramic Society* vol. 34, (3) 641-651.

Utilizing the phonon glass electron crystal concept to improve the thermoelectric properties of combined Yb-stuffed and Te-substituted CoSb₃.

. *Scripta Materialia* vol. 72-73, 63-66.

High field ZnO varistors prepared by spark plasma sintering.

. *Advances in Applied Ceramics* vol. 113, (2) 94-97.

Reply to the Comment on The Effect of Barium Substitution on the Ferroelectric Properties of Sr₂Nb₂O₇ Ceramics [J. Am. Ceram. Soc., 96 [4] 1163-1170 (2013)].

. *Journal of The American Ceramic Society* vol. 97, (2) 662-663.

2013

MgAl₂O₄-LaCr_{0.5}Mn_{0.5}O₃ composite ceramics for high temperature NTC thermistors.

. *Journal of Materials Science Materials in Electronics* vol. 24, (11) 4452-4456.

Effect of grain size on domain structures, dielectric and thermal depoling of Nd-substituted bismuth titanate ceramics.

. *Applied Physics Letters* vol. 103, (18).

Effects of zinc substitution on the dielectric properties of Ca₅Nb₄TiO₁₇ microwave ceramics.

. *Journal of Advanced Dielectrics* vol. 3, (04). World Scientific Publishing.

Effect of donor dopants cerium and tungsten on the dielectric and electrical properties of high Curie point ferroelectric strontium niobate.

. *Ceramics International* vol. 39, (7) 7669-7675.

Mechanical properties of graphene platelet-reinforced alumina ceramic composites.

. *Ceramics International* vol. 39, (6) 6215-6221.

Dielectric relaxation, lattice dynamics and polarization mechanisms in Bi_{0.5}Na_{0.5}TiO₃-based lead-free ceramics.

. *Journal of Applied Physics* vol. 114, (1).

Microwave dielectric properties of CaO-La₂O₃-Nb₂O₅-TiO₂ ceramics.

. *Journal of Materials Science Materials in Electronics* vol. 24, (6) 1947-1954.

Piezoelectric and dielectric properties of Ce substituted La₂Ti₂O₇ ceramics.

. *Journal of The European Ceramic Society* vol. 33, (5) 1001-1008.

The effect of barium substitution on the ferroelectric properties of Sr₂Nb₂O₇ Ceramics.

. *Journal of The American Ceramic Society* vol. 96, (4) 1163-1170.

Reverse boundary layer capacitor model in glass/ceramic composites for energy storage applications.

. *Journal of Applied Physics* vol. 113, (2).

Effect of donor dopants cerium and tungsten on the dielectric and electrical properties of high Curie point ferroelectric strontium niobate.

. *Ceramics International*.

Ferroelectricity of Pr₂Ti₂O₇ ceramics with super high Curie point.

. *Advances in Applied Ceramics* vol. 112, (2) 69-74.

Effect of Fe Substitution on Thermoelectric Properties of Fe_xIn_{4-x}Se₃ Compounds.

. *Journal of Electronic Materials* vol. 42, (4) 675-678.

Active ferroelectricity in nanostructured multiferroic BiFeO₃ bulk ceramics.

. *Journal of Materials Chemistry C* vol. 1, (36) 5628-5631.

Contribution of piezoelectric effect, electrostriction and ferroelectric/ferroelastic switching to strain-electric field response of dielectrics.

. *Journal of Advanced Dielectrics* vol. 3, (01). World Scientific Publishing.

2012

Microwave dielectric properties of La₃Ti₂TaO₁₁ ceramics with perovskite-like layered structure.

. *Journal of The European Ceramic Society* vol. 32, (16) 4015-4020.

Toughening of zirconia/alumina composites by the addition of graphene platelets.

. *Journal of The European Ceramic Society* vol. 32, (16) 4185-4193.

Ferroelectric ceramics with enhanced remnant polarization by ordered coalescence of nano-crystals.

. *Journal of Materials Chemistry* vol. 22, (44) 23547-23552.

Reversibility in electric field-induced transitions and energy storage properties of bismuth-based perovskite ceramics.

. *Journal of Physics D Applied Physics* vol. 45, (35).

Spherical instrumented indentation of porous nanocrystalline zirconia.

. *Journal of The European Ceramic Society* vol. 32, (1) 123-132.

Phase stability and rapid consolidation of hydroxyapatite-zirconia nano-coprecipitates made using continuous hydrothermal flow synthesis.

. *Journal of Biomaterials Applications* vol. 27, (1) 79-90.

Analysis of femtosecond laser surface patterning on bulk single-crystalline diamond.

. *Journal of Experimental Nanoscience* vol. 7, (6) 662-672.

Kinetics of Densification and Grain Growth of Pure Tungsten During Spark Plasma Sintering.

. *Metallurgical and Materials Transactions B-Process Metallurgy and Materials Processing Science* vol. 43, (6) 1608-1614.

2011

Ferroelectric domain structures and electrical properties of fine-grained lead-free sodium potassium niobate ceramics.

. *Journal of The American Ceramic Society* vol. 94, (10) 3391-3396.

Magneto-electric properties of multiferroic $\text{Pb}(\text{Zr}_{0.52}\text{Ti}_{0.48})\text{O}_3\text{-NiFe}_2\text{O}_4$ nanoceramic composites.

. *Journal of The American Ceramic Society* vol. 94, (8) 2311-2314.

High-strength nanograined and translucent hydroxyapatite monoliths via continuous hydrothermal synthesis and optimized spark plasma sintering.

. *Acta Biomater* vol. 7, (2) 791-799.

THE CONTRIBUTION OF ELECTRICAL CONDUCTIVITY, DIELECTRIC PERMITTIVITY AND DOMAIN SWITCHING IN FERROELECTRIC HYSTERESIS LOOPS.

. *J. Adv Dielectrics* vol. 1, 107-118.

2010

Effect of point defects on thermal depoling behavior of bismuth layer-structured ferroelectric ceramics.

. *J Appl Phys* vol. 108, (9).

Microstructure and electrical properties of Aurivillius phase $(\text{CaBi}_2\text{Nb}_2\text{O}_9)_{(1-x)}(\text{BaBi}_2\text{Nb}_2\text{O}_9)_x$ solid solution.

. *J Appl Phys* vol. 108, (1).

Highly conductive low nickel content nano-composite dense cermets from nano-powders made via a continuous hydrothermal synthesis route.

. *Solid State Ionics* vol. 181, (17-18) 827-834.

The sintering and grain growth behaviour of ceramic-carbon nanotube nanocomposites.

. *Compos Sci Technol* vol. 70, (6) 947-952.

High temperature lead-free relaxor ferroelectric: Intergrowth Aurivillius phase $\text{BaBi}_2\text{Nb}_2\text{O}_9\text{-Bi}_4\text{Ti}_3\text{O}_{12}$ ceramics.

. *Journal of Applied Physics* vol. 107, (10).

Piezoelectric Strontium Niobate and Calcium Niobate Ceramics with Super-High Curie Points.

. *J Am Ceram Soc* vol. 93, (5) 1409-1413.

Structural and chemical stability of multiwall carbon nanotubes in sintered ceramic nanocomposite.

. *Adv Appl Ceram* vol. 109, (4) 240-245.

Textured high Curie point piezoelectric ceramics prepared by spark plasma sintering.

. *Adv Appl Ceram* vol. 109, (3) 139-142.

Low temperature consolidated lead-free ferroelectric niobate ceramics with improved electrical properties.

. *J Mater Res* vol. 25, (2) 240-247.

Stability of Nanocrystalline Spark Plasma Sintered 3Y-TZP.

. *Materials* vol. 3, (2) 800-814.

Electrically conductive alumina-carbon nanocomposites prepared by Spark Plasma Sintering.

. *Journal of The European Ceramic Society* vol. 30, (2) 153-157.

2009

Degradation resistance of 3Y-TZP ceramics sintered using spark plasma sintering.

. *IOP Conference Series Materials Science and Engineering* vol. 5,.

Piezoelectric and Ferroelectric Properties of Bismuth Tungstate Ceramics Fabricated by Spark Plasma Sintering.

. *J Am Ceram Soc* vol. 92, (12) 3108-3110.

Piezoelectric Ceramics with Super-High Curie Points.

. *J Am Ceram Soc* vol. 92, (10) 2270-2275.

The grain size effect on the properties of Aurivillius phase Bi_{3.15}Nd_{0.85}Ti₃O₁₂ ferroelectric ceramics.

. *Nanotechnology* vol. 20, (38).

The grain size effect on the properties of Aurivillius phase Bi_{3.15}Nd_{0.85}Ti₃O₁₂ ferroelectric ceramics.

. *Nanotechnology* vol. 20, (38).

Fabrication and properties of dense ex situ magnesium diboride bulk material synthesized using spark plasma sintering.

. *Supercond Sci Tech* vol. 22, (9).

The effect of Nd substitution on the electrical properties of Bi₃NbTiO₉ Aurivillius phase ceramics.

. *J Appl Phys* vol. 106, (4).

High-temperature ferroelectric phase transition observed in multiferroic Bi_{0.91}La_{0.05}Tb_{0.04}FeO₃.

. *Applied Physics Letters* vol. 95, (1).

2008

Effect of a site substitution on the properties of CaBi₂Nb₂O₉ ferroelectric ceramics.

. *Journal of The American Ceramic Society* vol. 91, (9) 2928-2932.

Dimethylformamide: an effective dispersant for making ceramic-carbon nanotube composites.

. *Nanotechnology* vol. 19, (19).

Luminescence of Sr₂SiO_{4-x}N_{2x/3} : Eu²⁺ phosphors prepared by spark plasma sintering.

. *J Electrochem Soc* vol. 155, (2) J58-J61.

2007

Dielectric, piezoelectric, and ferroelectric properties of grain-orientated Bi_{3.25}La_{0.75}Ti₃O₁₂ ceramics.

. *J Appl Phys* vol. 102, (10).

Effect of annealing on dielectric behavior and electrical conduction of W⁶⁺ doped Bi₃TiNbO₉ ceramics.

. *Appl Phys Lett* vol. 90, (21).

2006

Lanthanum distribution and dielectric properties of Bi_{3-x}La_xTiNbO₉ bismuth layer-structured ceramics.

. *Scripta Mater* vol. 55, (9) 791-794.

Effect of texture on dielectric properties and thermal depoling of Bi₄Ti₃O₁₂ ferroelectric ceramics.

. *J Appl Phys* vol. 100, (7).

B-site donor and acceptor doped Aurivillius phase Bi₃NbTiO₉ ceramics.

. *J Eur Ceram Soc* vol. 26, (13) 2785-2792.

Dielectric relaxation of La³⁺-modified Bi₃TiNbO₉ Aurivillius phase ceramics.

. *J Am Ceram Soc* vol. 89, (9) 2939-2942.

Orientation dependence of dielectric and relaxor behaviour in Aurivillius phase BaBi₂Nb₂O₉ ceramics prepared by spark plasma sintering.

. *J Mater Sci-Mater El* vol. 17, (9) 657-661.

Doping effects on the electrical conductivity of bismuth layered Bi₃TiNbO₉-based ceramics.

. *J Appl Phys* vol. 100, (4).

Structural and electrical properties of W⁶⁺-doped Bi₃TiNbO₉ high-temperature piezoceramics.

. *J Am Ceram Soc* vol. 89, (5) 1756-1760.

2005

Thermal depoling of high Curie point Aurivillius phase ferroelectric ceramics.

. *Appl Phys Lett* vol. 87, (8).

A LeadFree HighCuriePoint Ferroelectric Ceramic, CaBi₂Nb₂O₉.

. *Cheminform* vol. 36, (28) no-no.Wiley.

A lead-free high-Curie-point ferroelectric ceramic, CaBi₂Nb₂O₉.

. *Adv Mater* vol. 17, (10) 1261-+.

Effective grain alignment in Bi₄Ti₃O₁₂ ceramics by superplastic-deformation-induced directional dynamic ripening.

. *Adv Mater* vol. 17, (6) 676-+.

Dielectric properties of single crystal diamond.

. *Semicond Sci Tech* vol. 20, (3) 296-298.

2004

The effect of (Li,Ce) and (K,Ce) doping in Aurivillius phase material CaBi₄Ti₄O₁₅.

. *Mater Res Bull* vol. 39, (9) 1237-1246.

Grain orientation effects on the properties of a bismuth layer-structured ferroelectric (BLSF) Bi₃NbTiO₉ solid solution.

. *J Am Ceram Soc* vol. 87, (4) 602-605.

2003

Preparation and electrical properties of bismuth layer-structured ceramic Bi₃NbTiO₉ solid solution.

. *Mater Res Bull* vol. 38, (2) 241-248.

2002

Influence of sintering temperature on the properties of high T_c bismuth layer structure ceramics.

. *Mat Sci Eng B-Solid* vol. 88, (1) 62-67.

2001

Formation of magnesium niobates in the MgO-Nb₂O₅ system and the effects of Fe₂O₃.

. *J Mater Sci Lett* vol. 20, (24) 2189-2191.

Formation of columbite-type precursors in the mixture of MgO-Fe₂O₃-Nb₂O₅ and the effects on fabrication of perovskites.

. *Mater Lett* vol. 51, (6) 490-499.

Effects of A-site (NaCe) substitution with Na-deficiency on structures and properties of CaBi₄Ti₄O₁₅-based high- Curie-temperature ceramics.

. *Jpn J Appl Phys 1* vol. 40, (11) 6501-6505.

Effects of Cr₂O₃ addition on the piezoelectric properties and microstructure of PbZr_xTiy(Mg_{1/3}Nb_{2/3})(1-x-y)O-3 ceramics.

. *J Eur Ceram Soc* vol. 21, (6) 703-709.

Effects of processing routes on structures and dielectric properties of lead iron niobate-lead magnesium niobate binary system.

. *Jpn J Appl Phys 1* vol. 40, (4A) 2348-2356.

Effects of processing routes on structures and dielectric properties of lead iron niobate-lead magnesium niobate binary system.

. *Japanese Journal of Applied Physics Part 1 Regular Papers and Short Notes and Review Papers* vol. 40, (4 A) 2348-2356.

2000

A-Site (MCe) Substitution Effects on the Structures and Properties of CaBi₄Ti₄O₁₅ Ceramics.

. *Japanese Journal of Applied Physics* vol. 39, (11R).IOP Publishing.

Study on Low Frequency Internal Friction for Pb(Zr,Ti)O₃ Ferroelectric Ceramics.

. *Physica Status Solidi (a) Applications and Materials Science* vol. 179, (1) 275-283.Wiley.

Anomalous internal friction in lead metaniobate ceramics.

. *Journal of Applied Physics* vol. 87, (6) 3186-3188.Aip Publishing.

Low-frequency internal friction study on modified lead metaniobate ceramics.

. *Chinese Physics B* vol. 9, (2) 149-152.IOP Publishing.