

Prof John Stark

BSc(Exon) MSc(Man) PhD(Lond) FRAS FRAeS

School of Engineering and Materials Science
Queen Mary University of London
Mile End Road
London E1 4NS

tel: +44 (0)20 7882 8875

email: j.p.w.stark@qmul.ac.uk web: www.sems.qmul.ac.uk/j.p.w.stark

2019

Scaling Laws for Transition from Varicose to Whipping Instabilities in Electrohydrodynamic Jetting.

Xia HH, Ismail A, Yao J and Stark J. *Physical Review Applied* vol. 12, (1). American Physical Society (Aps).

2018

Breakup length of electrified liquid jets: Scaling laws and applications.

ISMAIL AS, YAO J, XIA HH and STARK J. *Physical Review Applied*. American Physical Society.

2014

Microfabricated electrospray emitter arrays with integrated extractor and accelerator electrodes for the propulsion of small spacecraft.

Dandavino S, Ataman C, Ryan CN, Chakraborty S, Courtney D, Stark JPW and Shea H. *Journal of Micromechanics and Microengineering* vol. 24, (7).

Dispersion of nano-Au suspension using novel pulsed jet nanoelectrospraying approach.

Wang K and Stark J. *Materials Letters* vol. 123, 120-123.

The flow rate sensitivity to voltage across four electrospray modes.

Ryan CN, Smith KL and Stark JPW. *Applied Physics Letters* vol. 104, (8).

Electrospray pulsation: A diagnostic to understand cone-jet stability and minimum flow.

Stark JPW, Alexander MS and Smith KL. *Journal of Applied Physics* vol. 115, (4).

2012

The influence of geometry on the flow rate sensitivity to applied voltage within cone-jet mode electrospray.

Ryan CN, Smith KL and Stark JPW. *Journal of Applied Physics* vol. 112, (11).

Characterization of multi-jet electrospray systems.

Ryan CN, Smith KL and Stark JPW. *Journal of Aerosol Science* vol. 51, 35-48.

Direct fabrication and morphology of metallic micropatterns by pulsed jet nanoelectrospraying of silver nano-ink.

Wang K and Stark JPW. *Journal of Coatings Technology and Research* vol. 9, (3) 317-322.

2011

Nozzle size effects on the nanoelectrospraying of Au nanocolloid in a fully voltage-controlled form.

Wang K and Stark J. *Sensors and Actuators, a: Physical* vol. 165, (2) 338-341.

Electrospray deposited fibronectin retains the ability to promote cell adhesion.

Martyn SV, Heywood HK, Rockett P, Paine MD, Wang MJ, Dobson PJ, Sheard SJ, Lee DA and Stark JPW. *J Biomed Mater Res B* vol. 96B, (1) 110-118.

2010

Voltage effects on the nanoelectrospray characteristics in fully voltage-controlled atomisation of gold nanocolloids.

Wang K and Stark JPW. *Anal Chim Acta* vol. 679, (1-2) 81-84.

A full voltage-controlled nanoelectrospray system and its steady characteristic analysed by empirically equivalent circuit method.

Wang K, Tan Z, Ryan C, Smith K, Paine M and Stark J. *Sensors and Actuators, B: Chemical* vol. 147, (2) 618-621.

Direct fabrication of electrically functional microstructures by fully voltage-controlled electrohydrodynamic jet printing of silver nano-ink.

Wang K and Stark JPW. *Appl Phys a-Mater* vol. 99, (4) 763-766.

Deposition of colloidal gold nanoparticles by fully pulsed-voltage- controlled electrohydrodynamic atomisation.

Wang K and Stark JPW. *Journal of Nanoparticle Research* vol. 12, (3) 707-711.

2009

Freeform fabrication of metallic patterns by unforced electrohydrodynamic jet printing of organic silver ink.

Wang K, Paine MD and Stark JPW. *J Mater Sci-Mater El* vol. 20, (11) 1154-1157.

Effect of emitter geometry on flow rate sensitivity to voltage in cone jet mode electrospray.

Ryan CN, Smith KL, Alexander MS and Stark JPW. *Journal of Physics D: Applied Physics* vol. 42, (15).

Fully voltage-controlled electrohydrodynamic jet printing of conductive silver tracks with a sub- 100 ?m linewidth.

Wang K, Paine MD and Stark JPW. *Journal of Applied Physics* vol. 106, (2).

Tailoring the hydraulic impedance of out-of-plane micromachined electrospray sources with integrated electrodes.

Krpoun R, Smith KL, Stark JPW and Shea HR. *Applied Physics Letters* vol. 94, (16).

2008

Inexpensive optically isolated nanoammeter for use with micro-Newton electric propulsion technology.

Aplin KL, Smith KL, Firth JG, Kent BJ, Alexander MS and Stark JPW. *Journal of Propulsion and Power* vol. 24, (4) 891-895.

2007

High-aspect-ratio silica nozzle fabrication for nano-emitter electrospray applications.

Wang L, Stevens R, Malik A, Rockett P, Paine M, Adkin P, Martyn S, Smith K, Stark J and Dobson P. *Microelectronic Engineering* vol. 84, (5-8) 1190-1193.

A high accuracy technique to measure the electrical conductivity of liquids using small test samples.

Wu JP and Stark JPW. *J Appl Phys* vol. 101, (5).

Voltage-modulated flow rate for precise thrust control in colloid electrospray propulsion.

Alexander MS, Smith KL, Paine MD and Stark JPW. *Journal of Propulsion and Power* vol. 23, (5) 1042-1048.

Controlled electrospray pulsation for deposition of femtoliter fluid droplets onto surfaces.

Paine MD, Alexander MS, Smith KL, Wang M and Stark JPW. *Journal of Aerosol Science* vol. 38, (3) 315-324.

Nozzle and liquid effects on the spray modes in nanoelectrospray.

Paine MD, Alexander MS and Stark JPW. *Journal of Colloid and Interface Science* vol. 305, (1) 111-123.

2006

Evaluation of band structure and concentration of ionic liquid BMImBF₄ in molecular mixtures by using second derivatives of FTIR spectra.

Wu JP, Wang MJ and Stark JPW. *J Quant Spectrosc Ra* vol. 102, (2) 228-235.

The role of molar conductivity in electrospray cone-jet mode current scaling.
Smith KL, Alexander MS and Stark JPW. *Journal of Applied Physics* vol. 100, (1).

Electrospray performance of microfabricated colloid thruster arrays.
Alexander MS, Stark J, Smith KL, Stevens B and Kent B. *J Propul Power* vol. 22, (3) 620-627.

Pulsation modes and the effect of applied voltage on current and flow rate in nanoelectrospray.
Alexander MS, Paine MD and Stark JPW. *Analytical Chemistry* vol. 78, (8) 2658-2664.

Voltage effects on the volumetric flow rate in cone-jet mode electrospraying.
Smith KL, Alexander MS and Stark JPW. *Journal of Applied Physics* vol. 99, (6).

Measurement of low frequency relative permittivity of room temperature molten salts by triangular waveform voltage.
Wu JP and Stark JPW. *Meas Sci Technol* vol. 17, (4) 781-788.

The sensitivity of volumetric flow rate to applied voltage in cone-jet mode electrospray and the influence of solution properties and emitter geometry.
Smith KL, Alexander MS and Stark JPW. *Physics of Fluids* vol. 18, (9).

2005

Fabrication and operation of microfabricated emitters as components for a colloid thruster.
Stark J, Stevens B, Alexander M and Kent B. *Journal of Spacecraft and Rockets* vol. 42, (4) 628-639.

A low-cost approach for measuring electrical conductivity and relative permittivity of liquids by triangular waveform voltage at low frequencies.
Wu JP and Stark JPW. *Meas Sci Technol* vol. 16, (5) 1234-1240.

2004

Controlled electrospray for tissue engineering applications.
Paine MD and Stark JPW. *Materials Research Society Symposium Proceedings* vol. 860, 67-72.

2002

The direct simulation Monte Carlo of flows composed of asymmetric potential scatterers.
Alves N and Stark J. *Phys Fluids* vol. 14, (4) 1403-1413.

2001

Direct simulation of meteoroids and space debris flux on LDEF spacecraft surfaces.
Miao JQ and Stark JPW. *Planet Space Sci* vol. 49, (9) 927-935.

Direct simulation of apex enhancement on the flux onto European retrievable carrier.
Miao JQ and Stark JPW. *J Spacecraft Rockets* vol. 38, (4) 594-600.

Evolution of debris clouds to microscopically chaotic motion.
Stark JPW. *J Spacecraft Rockets* vol. 38, (4) 554-562.

1999

Direct simulation of space debris evolution.
Wang LQ and Stark JPW. *J Spacecraft Rockets* vol. 36, (1) 114-123.